

For finishing use WOC (ae) .01 up to .1xd, use SFM from .25xd column, do not increase IPT from table values

Surface feet per minute - SFM				
High Speed Milling			Rough	Slot
DOC 2xd			DOC 1xd	
WOC .05xd	WOC .1xd	WOC .25xd	WOC .4 to .9xd	WOC 1xd

$$RPM = \frac{SFM}{d_1} \times 3.82$$

$$IPM = \text{No. of teeth} \times IPT \times RPM$$

Feed Rate Inch per Tooth - IPT								
d1 End Mill Diameter								
1/8 3.17mm	1/4 6.35mm	5/16 7.94mm	3/8 9.52mm	1/2 12.70mm	5/8 15.87mm	3/4 19.05mm	1 25.40mm	
Multiply IPT x this factor based on WOC								
.0005	.0010	.0013	.0016	.0021	.0027	.0030	.0044	
.0005	.0010	.0013	.0016	.0021	.0027	.0030	.0044	
.0005	.0009	.0011	.0015	.0020	.0023	.0030	.0040	
.0003	.0005	.0007	.0009	.0012	.0016	.0019	.0024	
.0003	.0007	.0009	.0011	.0015	.0020	.0023	.0032	
.0003	.0006	.0007	.0010	.0013	.0016	.0019	.0028	
.0003	.0005	.0007	.0009	.0012	.0016	.0019	.0024	
.0002	.0004	.0005	.0007	.0009	.0012	.0015	.0020	
.0003	.0007	.0009	.0011	.0015	.0020	.0023	.0032	
.0005	.0009	.0012	.0015	.0020	.0023	.0030	.0040	
.0004	.0008	.0010	.0012	.0017	.0020	.0026	.0032	
.0008	.0015	.0020	.0024	.0033	.0039	.0049	.0064	
.0007	.0013	.0016	.0021	.0028	.0035	.0041	.0056	
.0007	.0013	.0016	.0021	.0028	.0035	.0041	.0056	
.0005	.0010	.0013	.0017	.0023	.0027	.0034	.0048	

Material	Hardness	TYPE	SFM				
			2.5	2.3	1.5	1	1
Structural + free-cutting steels, unalloyed heat-treatable + case hardened steels A283, 1151, 1215, L10, 10Lxx, 11Lxx, 12Lxx, 41Lxx, 51Lxx, 86Lxx, 86Lxx, 10xx	up to 28 HRc	2, 3, 4 Flute	840	760	640	460	400
Free-cutting steels, unalloyed case hardened steels, nitriding steels 1151, 1215, L10, 10Lxx, 11Lxx, 12Lxx, 41Lxx, 51Lxx, 86Lxx, 86Lxx, 10xx, 11xx	28 to 38 HRc	2, 3, 4 Flute	760	680	580	425	360
Alloyed heat-treatable, tool and high speed steels 13xx, 2340, 31xx, 32xx, 33xx, 34xx, 40xx, 41xx, 43xx, 4640, 50xx, 51xx, 61xx, 71xx, 86xx, 87xx, 92xx, 98xx, 98xx, Ax, Ox, Dx, Hxx, Lx, Wx, Mx, Tx	28 to 44 HRc	2, 3, 4 Flute	630	570	480	360	300
Hardened Steels Carbon and Alloy Steels, Tool & Die Steels	Up to 54 HRc	2, 3, 4 Flute	230	200	160	160	115
Stainless steel 303, 410, 420F, 430, 430F, 416	Up to 28 HRc	2, 3, 4 Flute	550	500	325	325	260
Stainless steel 304, 304L, 420, 17-4PH, 17-7PH, 15-5PH, 13-8PH	up to 28 HRc	2, 3, 4 Flute	380	340	230	230	180
Stainless steel 310, 316, 316B, 316L, 317, Duplex	over 28 HRc	2, 3, 4 Flute	320	290	230	230	150
Titanium Alloys 6Al-4V, 5Al-2.5 Sn, 6Al-2Sn-4Zr-6Mo, 3Al-8V-6Cr4Mo-4Zr, 10V-2Fe-3Al, 13V-11Cr-3Al	up to 42 HRc	2, 3, 4 Flute	270	250	165	165	130
High-Temperature Alloys Inconel, Nimonic, Monel, Hastelloy, Waspalloy, A286, Rene 41, Udimet, Stellite	up to 42 HRc	2, 3, 4 Flute	170	150	130	130	80
Cast iron, grey cast iron, spheroidal graphite and malleable cast iron 0.6010 EN-GJ100 (GG10), 0.6020 EN-GJL-200 (GG20), 0.7050 EN-GJS-500-7 (GGG50), 0.8535 EN-GJMW-350-4 (GTW35)	up to 240 HB 30	2, 3, 4 Flute	760	680	580	425	360
Cast iron, grey cast iron, spheroidal graphite and malleable cast iron 0.6025 EN-GJ250 (GG25), 0.6035 EN-GJL-350 (GG35), 0.7070 EN-GJS-700-2 (GGG70), 0.8170 EN-GJMB-700-2 (GTS70)	over 240 HB 30	2, 3, 4 Flute	650	590	500	360	310
Aluminum, Al-wrought alloys, Al-alloys 2024, 6061, 7075, 1050, 6351, 5005, 2017, 7075	up to 3% Si	2, 3, 4 Flute	2060	1860	1570	1150	980
Aluminium-cast alloys 3.2131 G-AISI5Cu1, 3.2153 G-AISI7Cu3, 3.2573 G-AISI9, 3.2581 G-AISI12, 3.2583 G-AISI12Cu, - G-AISI12CuNiMg	over 3% Si	2, 3, 4 Flute	1100	1000	840	625	525
Magnesium-alloys MgMn2, G-MgAl8Zn1, G-MgAl6Zn3	—	2, 3, 4 Flute	860	780	660	690	410
Non-ferrous metals (copper, short- or long-chipping brass or bronze)	up to 28 HRc	2, 3, 4 Flute	1210	1090	920	950	575

UNI-PRO End Mills (4-Flute) - Inch - XL Long Length



center cutting



Tool material

Solid Carbide

Surface finish

bright

FIREX®


Series

3151

3155

Application group	Material examples	Ideal for
P	Steel	●
M	Stainless steel	●
K	Cast iron	●
N	Aluminum	●
S	Ni / Ti alloys	○
H	Hardened steel	--
●=Optimal ○=Secondary		

Speed and Feed data found on page 297



d1 h10	d2 h6	l1	l2	c	No. of Flutes	Code no.	EDP Number	
inch	inch	inch	inch	inch x 45°				
3/16	3/16	3	1 1/4	0.002	4	4.760	9031510047600	9031550047600
1/4	1/4	4	1 5/8	0.004	4	6.350	9031510063500	9031550063500
5/16	5/16	4	1 5/8	0.004	4	7.940	9031510079400	9031550079400
3/8	3/8	4	1 5/8	0.004	4	9.520	9031510095200	9031550095200
7/16	7/16	5	2	0.006	4	11.110	9031510111100	9031550111100
1/2	1/2	6	3	0.006	4	12.700	9031510127000	9031550127000
5/8	5/8	6	3	0.006	4	15.870	9031510158700	9031550158700
3/4	3/4	6	3	0.006	4	19.050	9031510190500	9031550190500
1	1	6	3	0.012	6	25.400	9031510254000	9031550254000