

— FOR METRIC FLAT HEAD SOCKET CAP SCREWS —

SpyroTec 90°

Ideal for fasteners with 90° heads.
Perfect choice for general deburring and
chamfering of holes.

from p. 8

NEW

SpyroTec 90°
Sets now with Ø 25mm



Series


Tool material

Coating

TiAIN **A**


Shank form

cyl.



- long version for recessed machining points
- 3 different convex cutting edges
- low-vibration cutting processes
- for round and chatter-free countersinking
- considerably lower feed force required
- for universal application

Operating parameters pg. 22

10



Series # 5503, 5670, 5671, 5672, 5673


Material group	Hardness		SFM	Feed Rate - IPR								
	HRC	Bhn		6.30 mm	8.00 mm	10.00 mm	12.50 mm	16.00 mm	20.00 mm	25.00 mm	31.50 mm	41.00 mm
				0.248 In.	0.315 In.	0.394 In.	0.492 In.	0.630 In.	0.787 In.	0.984 In.	1.240 In.	1.614 In.
Common structural steels	-	≤ 150	120	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 32	≤ 301	115	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
Free-cutting steels	≤ 25	≤ 255	120	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 32	≤ 301	115	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
Unalloyed heat-treatable steels	≤ 20	≤ 220	120	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 25	≤ 255	115	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 32	≤ 301	75	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
Alloyed heat-treatable steels	≤ 32	≤ 301	55	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 43	≤ 402	45	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
Unalloyed case hardened steels	≤ 25	≤ 255	95	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
Alloyed case hardened steels	≤ 32	≤ 301	55	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 43	≤ 402	40	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
Nitriding steels	≤ 32	≤ 301	55	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
	≤ 43	≤ 402	45	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Tool steels	≤ 25	≤ 255	65	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
	≤ 43	≤ 402	55	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
High speed steels	≤ 43	≤ 402	55	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Spring steels	≤ 38	≤ 354	40	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Hardened steels	≤ 48	≤ 460										
	≤ 66	-										
Stainless steels, sulphured	≤ 28	≤ 273	60	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
	≤ 36	≤ 337	45	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
	≤ 46	≤ 435	50	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Cast iron	≤ 23	≤ 242	95	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 38	≤ 354	60	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
Spheroidal graphite iron and malleable cast iron	≤ 23	≤ 242	80	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 38	≤ 354	75	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
Chilled cast iron	≤ 38	≤ 354	30	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
New cast materials GGV	≤ 20	≤ 220	80	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	≤ 32	≤ 301	50	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
New cast materials ADI	≤ 32	≤ 301										
	≤ 43	≤ 402										
Special alloys	≤ 54	≤ 549	30	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Ti and Ti-alloys	≤ 25	≤ 255	55	0.0030	0.0030	0.0035	0.0040	0.0045	0.0050	0.0060	0.0065	0.0085
	≤ 43	≤ 402	40	0.0015	0.0020	0.0025	0.0025	0.0030	0.0030	0.0035	0.0045	0.0055
Aluminium and Al-alloys	-	≤ 120	340	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Al wrought alloys	-	≤ 200	265	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Al cast alloys ≤ 10 % Si	-	≤ 180	150	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
	-	≤ 180	115	0.0045	0.0050	0.0055	0.0060	0.0065	0.0070	0.0085	0.0095	0.0110
Magnesium alloys	-	≤ 120	375	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Copper, low-alloyed	-	≤ 150	225	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Brass, short-chipping	-	≤ 180	300	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
	-	≤ 180	190	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Bronze, short-chipping	-	≤ 180	115	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
	≤ 25	≤ 255	100	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Bronze, long-chipping	≤ 25	≤ 255	90	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
	≤ 32	≤ 301	75	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Duroplastics			115	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Thermoplastics			150	0.0060	0.0065	0.0065	0.0075	0.0085	0.0090	0.0100	0.0120	0.0135
Reinforced plastics - Kevlar												
Reinforced plastics - GFK / CFK												

SpyroTec

THE INNOVATIVE, TWISTED HSS AND HSCO COUNTERSINK

The axial and radial forces that occur during countersinking operations are significantly reduced due to the unique geometry of the SpyroTec cutting edges. The convex form and variable pitch of the helical cutting edges results in a stable countersinking process with minimal vibration, even when using

a hand drill. Round, precise, chatter-free countersinking is guaranteed. The TiAlN coating ensures higher wear resistance and thermal protection, which guarantees longer tool life in many different materials and applications.



- standard program
- 90°, 82°, and 60° countersinks
- round shank version
- tri-flat shank version
- long length round shank version



Countersinking with standard countersink



SpyroTec



CONVEX CUTTING EDGES

Three different convex cutting edges in combination with three unequal helix angles enable extremely stable and low-vibration cutting processes without any chatter marks.

TiAlN COATING

The TiAlN coating provides high hardness and excellent thermal protection.


CUTTING MATERIAL

The high-quality HSS and HSCO substrates hold up well in high-temperature applications, providing long tool life in a wide variety of materials.



SPYROTEC – SPIRAL-FLUTED COUNTERSINKS

Suitable for countersinking the smallest allowable hole diameters and screw sizes listed below.



SpyroTec 90°

d1	smallest allowable hole Ø	for countersunk screws ISO 2009, 2010, 7046, 7047	for countersunk screws DIN 7991
6.300	2.00	-	M3
8.000	2.50	M4	-
8.300	2.50	-	M4
10.000	3.00	M5	-
10.400	3.00	-	M5
11.500	3.30	M6	-
12.400	3.30	-	M6
15.000	3.70	M8	-
16.500	3.70	-	M8
19.000	4.50	M10	-
20.500	4.50	-	M10
23.000	4.80	M12	-
25.000	4.80	-	M12
31.000	5.20	-	M16
40.000	12.00	-	M24

SpyroTec 82°

d1 frac.	Smallest hole - Ø to allow countersinking - inch
1/4	0.0830
5/16	0.1020
3/8	0.1100
1/2	0.1730
5/8	0.2010
3/4	0.2520
7/8	0.2720
1	0.2910
1 1/4	0.4090

SpyroTec 60°

d1	smallest hole - Ø to allow countersinking - mm
6.300	2.10
8.000	2.50
10.000	3.00
12.500	3.70
16.000	4.50
20.000	6.00
25.000	7.30

