

SPEED & FEED GUIDE



Optimum Performance

Series 2010, 2012, 2014, 2015

250 2 FLUTE SERIES NON-FERROUS

Material	Axial ↓	Radial →	SFM	1/8		1/4		5/16		3/8		1/2		5/8		3/4		
				RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	
N Aluminum, Brass, Copper 6061, 7050, 7075	.5 x D	1 x D	600	18336	44	9168	48	7334	53	6112	53	4584	55	3667	53	3056	53	
	1.25 x D	.3 x D	720	22003	66	11002	70	8801	77	7334	77	5501	80	4401	77	3667	77	
	1.5 x D	.1 x D	1200	36672	147	18336	150	14669	154	12224	154	9168	162	7334	155	6112	155	
	High Silicon Aluminum 4% - 13% A242, A319, A356, A390	.5 x D	1 x D	600	18336	37	9168	40	7334	44	6112	44	4584	46	3667	44	3056	44
		1.25 x D	.3 x D	720	22003	53	11002	56	8801	63	7334	63	5501	67	4401	64	3667	64
		1.5 x D	.1 x D	1200	36672	117	18336	121	14669	132	12224	132	9168	139	7334	133	6112	133

Series 2030, 2031, 2047, 2032, 2050, 2053

350 3 FLUTE SERIES NON-FERROUS

Material	Axial ↓	Radial →	SFM	1/8		1/4		5/16		3/8		1/2		5/8		3/4		
				RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	
N Aluminum, Brass, Copper 6061, 7050, 7075	.5 x D	1 x D	600	18336	66	9168	66	7334	79	6112	79	4584	83	3667	80	3056	80	
	1.25 x D	.3 x D	720	22003	99	11002	96	8801	115	7334	115	5501	121	4401	116	3667	116	
	1.5 x D	.1 x D	1200	36672	220	18336	193	14669	231	12224	231	9168	243	7334	233	6112	233	
	High Silicon Aluminum 4% - 13% A242, A319, A356, A390	.5 x D	1 x D	600	18336	55	9168	55	7334	66	6112	66	4584	69	3667	67	3056	67
		1.25 x D	.3 x D	720	22003	79	11002	79	8801	95	7334	95	5501	100	4401	96	3667	96
		1.5 x D	.1 x D	1200	36672	176	18336	165	14669	198	12224	198	9168	208	7334	200	6112	200

Series 2060

550 5 FLUTE SERIES NON-FERROUS

Material	Axial ↓	Radial →	SFM	1/8		1/4		5/16		3/8		1/2		5/8		3/4		
				RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	RPM	IPM	
N Aluminum, Brass, Copper 6061, 7050, 7075	.5 x D	.5 x D	600	18336	110	9168	110	7334	132	6112	132	4584	139	3667	133	3056	133	
	1.25 x D	.3 x D	720	22003	165	11002	160	8801	191	7334	191	5501	201	4401	193	3667	193	
	1.5 x D	.1 x D	1200	36672	367	18336	321	14669	385	12224	385	9168	404	7334	388	6112	388	
	High Silicon Aluminum 4% - 13% A242, A319, A356, A390	.5 x D	.5 x D	600	18336	92	9168	92	7334	110	6112	110	4584	116	3667	111	3056	111
		1.25 x D	.3 x D	720	22003	132	11002	132	8801	158	7334	158	5501	166	4401	160	3667	160
		1.5 x D	.1 x D	1200	36672	293	18336	275	14669	330	12224	330	9168	347	7334	333	6112	333

PERFORMANCE

Premium Carbide End Mills for Non-Ferrous Alloys



Series 2060 | 550 | 5FL | Square

Diameter	Shank Dia.	LOC	OAL	Bright EDP	ZrN EDP
1/4	1/4	3/8	2-1/2	315994	315997
1/4	1/4	3/4	2-1/2	316000	316002
1/4	1/4	1-1/4	3	316005	316009
5/16	5/16	7/16	2-1/2	316013	316016
5/16	5/16	13/16	2-1/2	316019	316021
5/16	5/16	1-1/4	3-1/2	316023	316026
3/8	3/8	1/2	2-1/2	316030	316033
3/8	3/8	1	2-1/2	316035	316039
3/8	3/8	1-1/4	3	316041	316044
3/8	3/8	2	4	316046	316048
1/2	1/2	5/8	3	316052	316056
1/2	1/2	1-1/4	3	316058	316061
1/2	1/2	2	4	316064	316068
1/2	1/2	3-1/4	6	316070	316073
5/8	5/8	3/4	3-1/2	316076	316079
5/8	5/8	1-5/8	3-1/2	316083	316087
5/8	5/8	2-1/2	5	316091	316095
3/4	3/4	1	4	316098	316102
3/4	3/4	1-5/8	4	316105	316108
3/4	3/4	2-1/4	5	316111	316113
3/4	3/4	3	6	316116	316120
1	1	1-1/4	5	316122	316126
1	1	2	5	316130	316132
1	1	2-1/2	5	316136	316139
1	1	3	6	316142	316146

More About the Series 2060

Designed for High Speed Profiling of Aluminum



★ Best ☆ Good