

DIAL TENSION GAGES

- Clockwise and counter-clockwise use
- For electronic and precision mechanical industry, such as measure contact pressure of relay, adjust the tension or compression of spring



ISF-TG3

SPECIFICATION

Part No.	ISF-TGD1	ISF-TGD3	ISF-TGD5	ISF-TG1	ISF-TG1D5	ISF-TG3	ISF-TG5
Capacity (N)	0.1	0.3	0.5	1	1.5	3	5
Graduation (N)	0.002	0.005	0.01	0.02	0.025	0.05	0.1
Accuracy	±2% (full scale)						
Dimension (L×W×H)	3.54×1.85×.74"						
Weight	.13lb						

DATA OUTPUT

DIGITAL BOTTLE CAP TORQUE TESTERS

- Measure the open and tighten torque of bottle cap
- Units: lbf.in, lbf.ft, N.m, N.cm, kgf.cm
- 1500 memories
- Wireless connection to printer
- Automatic power off
- LCD display with backlight
- Overload alarm
- With calibration function



IST-DCT20

software CD
(included)



printer (optional)



SPECIFICATION

Part No.	IST-DCT2	IST-DCT5	IST-DCT10	IST-DCT20
Load capacity	17.7lbf.in	44.3lbf.in	88.5lbf.in	177lbf.in
	—	3.68lbf.ft	7.4lbf.ft	14.7lbf.ft
Resolution	0.01lbf.in	0.01lbf.in	0.05lbf.in	0.1lbf.in
	—	0.001lbf.ft	0.005lbf.ft	0.01lbf.ft
Clamping range	.77~7.48" DIA			
Accuracy	±0.5% (of load capacity)			
Measuring mode	tracking, peak (max.), first peak, double peak, low and high limits with judgement			
Output	wireless and USB			
Power supply	built-in rechargeable battery			
Dimension	7.87×7.76×5.59"			
Weight	5.51lb			

STANDARD DELIVERY

Main unit	1 pc
AC/DC adapter	1 pc
USB cable and software	1 pc

OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
---------	----------------

two display modes

