




## LARGE RANGE DIAL TEST INDICATOR



2386-006A



Jeweled bearing ■ Carbide contact point

■ Two measuring directions

Anti magnetic body
Supplied with two clamps: 5/32" DIA and 3/8" DIA

■ Optional accessory: styli (page 77)

Part No.	Range	Graduation	Accuracy	Dial reading
2386-006A*	.06"	.0005"	±.0008"	0-15-0


<sup>\*</sup>Supplied with manufacturer inspection certificate traceable to NIST





## LARGE RANGE BACK PLUNGER TYPE DIAL TEST INDICATOR





- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: 5/32" DIA and 3/8" DIA

Optional accessory: styli (page 77)				
Part No.	Range	Graduation	Accuracy	Dial reading
2480-06*	.06"	.0005"	±.0008"	0-15-0
_				

<sup>\*</sup>Supplied with manufacturer inspection certificate traceable to NIST



3/8" DIA 5/32" DIA

## STYLI FOR DIAL TEST INDICATORS



6284-10

9/	M1 <u>.6x0.35mm</u>
Ø===	
	L

Part No.	For dial test indicator	Material of contact point	L	D
6284-91		carbide	.472"	.039" DIA
6284-92	2834-008	carbide	.472"	.079" DIA
6284-93		carbide	.472"	.118" DIA
6284-9	2380-31,2380-35, 2381-31, 2381-35, 2398-03, 2399-03	steel	.50"	.039" DIA
6284-10		carbide	.50"	.079" DIA
6284-11		ruby	.50"	.079" DIA
6284-12		carbide	.50"	.118" DIA
6284-13	2380-301, 2381-301	steel	.563"	.039" DIA
6284-14		carbide	.563"	.079" DIA
6284-15		ruby	.563"	.079" DIA
6284-16		carbide	.563"	.118" DIA

Part No.	For dial test indicator	Material of contact point	L	D
6284-94		carbide	.437"	.039" DIA
6284-95	2835-03	carbide	.437"	.079" DIA
6284-96		carbide	.437"	.118" DIA
6284-17		steel	1.020"	.039" DIA
6284-18	2383-35A	carbide	1.020"	.079" DIA
6284-19	2303-33A	ruby	1.020"	.079" DIA
6284-20		carbide	1.020"	.118" DIA
6284-65		steel	.50"	.039" DIA
6284-66	2386-006A,	carbide	.50"	.079" DIA
6284-67	2480-06	ruby	.50"	.079" DIA
6284-68		carbide	.50"	.118" DIA