

4 FLUTE • DOUBLE END CARBIDE DRILL POINT COUNTERSINK



SERIES: DC4DP

SIZE	SHK	OAL	TOOL	ANGLE/EDP#					
				60°	82°	90°	100°	110°	120°
1/8	1/8	1-1/2	DC4DP-1/8	18992	18833	18994	18996	18998	19000
3/16	3/16	2	DC4DP-3/16	19002	18835	19004	19006	19008	19010
1/4	1/4	2	DC4DP-1/4	19012	18837	19014	19016	19018	19020
5/16	5/16	2-1/2	DC4DP-5/16	19022	19071	19024	19026	19028	19030
3/8	3/8	2-1/2	DC4DP-3/8	19032	18840	19034	19036	19038	19040
1/2	1/2	3	DC4DP-1/2	19042	18842	19044	19046	19048	19050
5/8	5/8	3-1/2	DC4DP-5/8	19052	18843	19054	19056	19058	19060
3/4	3/4	4	DC4DP-3/4	19061	18845	19063	19065	19067	19069

- Drill and countersink with one tool.
 - Can save setup and production time by combining two operations into one.
- To order countersinks: Use the EDP # listed or add the angle to the end of the tool name (i.e. DHS1-1/4-90).

SPEED & FEED INFORMATION

Carbide Drills

SERIES: HDR, IDR, JDR, LDR, HDRNC

MATERIAL	ISO	CARBIDE SFM	HSSCO SFM	FEED RATE PER TOOTH (IPR)			
				1/16"	1/8"	1/4"	1/2"
Stainless Steels-Soft	M	80-300	20-40	0.0005	0.0005	0.0020	0.0040
Stainless Steels-Hard (PH)	M	40-100	15-25	0.0005	0.0005	0.0010	0.0015
Nickel Base Alloys	S	75-200	15-25	0.0005	0.0006	0.0010	0.0015
Inconel/Monel/Hastelloy	S	75-200	15-25	0.0005	0.0005	0.0010	0.0015
Titanium-Soft	S	80-350	20-25	0.0005	0.0020	0.0040	0.0050
Titanium-Hard	S	40-100	20-25	0.0005	0.0008	0.0020	0.0040
Low Carbon Steels	P	150-300	75-130	0.0005	0.0010	0.0020	0.0040
Die Steels	P	60-130	30-45	0.0005	0.0005	0.0020	0.0040
Hardened Steels > HRc 50	H	25-75	-	0.0005	0.0010	0.0020	0.0030
Cast Iron	K	100-300	60-110	0.0010	0.0020	0.0030	0.0050
Malleable Iron	K	65-200	40-80	0.0010	0.0020	0.0030	0.0050
Aluminium Alloys	N	100-400	150-250	0.0010	0.0020	0.0030	0.0050
Brass & Bronze	N	150-300	100-150	0.0005	0.0010	0.0020	0.0040
Copper	N	150-300	75-150	0.0010	0.0030	0.0050	0.0060
Magnesium	N	300-600	200-350	0.0015	0.0030	0.0050	0.0080
Plastics	N	150-450	70-150	0.0015	0.0030	0.0040	0.0060

Countersinks

MATERIAL	ISO	HSS SFM	COUNTERSINK TYPE	
			M42 8% COBALT WITH TiN SFM	CARBIDE SFM
Stainless Steels - Free Machining	M	30-80	40-100	80-125
Stainless Steels - Others	M	15-50	20-65	50-75
Inconels/Monels	S	30-50	40-65	50-75
Titaniums (6Al4V)	S	50-60	60-75	60-90
Steels Annealed	P	40-50	50-65	50-80
Steels HRc 18-24	P	30-40	40-50	40-60
Steels HRc 25-37	P	25-35	30-45	35-55
Mild Steels	P	70-100	85-125	80-170
Cast Iron	K	75-125	95-150	125-225
Malleable Iron	K	80-90	100-115	90-150
Aluminums Alloys	N	150-250	180-300	300-500
Brass (Bronze)	N	75-125	95-150	150-250
Magnesium	N	125-250	150-300	250-400
Plastics	N	100-250	125-300	250-400

► Multiple flute countersinks are designed for increased feed rates. A controlled feed rate will result in better surface finish.

► All Melin countersinks are manufactured on CNC grinders to ensure consistent and accurate flute spacing. Carbide countersinks should be used in rigid tool holders to maximize tool life.

All technical data provided are suggested starting points. They may be increased or decreased depending on machine condition, depth of cut, finish required, coolant, etc. Call our TECHNICAL SERVICE TEAM with questions.

SPEED & FEED INFORMATION

Calculations

End mill speed & feed formulas are the various individual equations that determine the proper overall machining setup or more specifically the speed of the cutting tool and the rate which it is fed into the work piece. Each individual formula is distinct in what it determines but coordinates with the others to ensure successful cutting tool application. You can visit the TECHNICAL section on www.melintool.com for more information.

INCH

$$\text{RPM} = \frac{\text{Revolutions Per Minute}}{3.82 \times \text{SFM} / \text{Tool Dia}}$$

$$\text{SFM} = \frac{\text{Surface Foot Per Minute}}{.262 \times \text{RPM} \times \text{Tool Dia}}$$

$$\text{CPT or IPT} = \frac{\text{Chip-Load Per Tooth}}{\text{IPM} / \text{RPM} / \text{No. Of Flutes}}$$

$$\text{IPM} = \frac{\text{Inches Per Minute}}{\text{CPT} \times \text{RPM} \times \text{No. Of Flutes}}$$

$$\text{MRRCI} = \frac{\text{Metal Removal Rate Cubic Inches}}{\text{IPM} \times \text{Axial Doc} \times \text{Radial Woc}}$$

$$\text{IPR} = \frac{\text{Inches Per Revolution}}{\text{IPM} / \text{RPM}}$$

METRIC

$$\text{RPM} = \frac{\text{Revolutions Per Minute}}{1000 \times \text{M/MIN} / (3.14 \times \text{D})}$$

$$\text{M/MIN} = \frac{\text{Meters Per Minute}}{(3.14 \times \text{D} \times \text{RPM}) / 1000}$$

$$\text{Fz OR CPT} = \frac{\text{Chip-Load Per Tooth}}{\text{Feedrate (mm) per MIN} / (\text{Z} \times \text{RPM})}$$

$$\text{VF OR FPM} = \frac{\text{Feedrate (mm) Per Minute}}{\text{Feedrate (mm) per Tooth} \times \text{Z} \times \text{RPM}}$$

$$\begin{aligned} \text{D} &= \text{Cutter Dia.} \\ \text{Z} &= \text{No. Of Teeth.} \end{aligned}$$

EQUIVALENTS & CONVERSIONS:

ABBREVIATIONS

RPM	Revolutions Per Minute
SFM	Surface Feet Per Minute
CPT	Chip Load Per Tooth
IPM	Inches Per Minute
V_f	Millimeters Per Minute
ae	Radial Width of Cut
ap	Axial Depth of Cut
Vc	Surface Meters Per Minute
Fz	Metric Chip Load Per Tooth

$$N, n \text{ or } \text{Min}^{-1} = \text{RPM}$$

$$Vc \text{ or } \text{M/MIN} = \text{SFM}$$

$$Fz \text{ or } \text{mm/TOOTH} = \text{CPT}$$

$$V_f \text{ or } \text{mm/MIN} = \text{IPM}$$

$$\text{SFM} / 3.281 = \text{M/MIN}$$

$$\text{M/MIN} \times 3.281 = \text{SFM}$$

$$\text{mm/MIN} / 25.4 = \text{IPM}$$

$$\text{mm/TOOTH} / 25.4 = \text{CPT}$$



IMPERIAL METRIC

$$\text{Inch} \times 25.4 = \text{Millimeter}$$

$$\text{Millimeter} \times .03937 = \text{Inch}$$