





COUNTERSINKS

6 FLUTE • CARBIDE COUNTERSINK



Carbide  MULTI°  BRIGHT  HRC <52  P M H K S H

- For highly abrasive and hard to machine materials. Applications in **cast iron, alloy steel, or glass reinforced plastics.**
- Carbide eliminates the high cost of tool changes in production situations.
- Rigid set up is a must - not suited for hand held applications.
- Tools 3/8" and larger have solid carbide heads on hardened steel shanks.
- See page 147 for Nose Diameter

SERIES: C6

| SIZE | SHK | OAL | TOOL | ANGLE/EDP# | | | | |
|-------|------|-------|----------|------------|-------|-------|-------|-------|
| | | | | 60° | 82° | 90° | 100° | 120° |
| 1/8 | 1/8 | 1-1/2 | C6-1/8 | 18368 | 18369 | 18370 | 18371 | 18372 |
| 3/16 | 3/16 | 1-1/2 | C6-3/16 | 18373 | 18374 | 18375 | 18376 | 18377 |
| 1/4 | 1/4 | 2 | C6-1/4 | 18378 | 18379 | 18380 | 18381 | 18382 |
| 5/16 | 1/4 | 2-1/2 | C6-5/16 | 18383 | 18384 | 18385 | 18386 | 18387 |
| 3/8 | 1/4 | 2-1/2 | C6-3/8 | 18388 | 18389 | 18390 | 18391 | 18392 |
| 1/2 | 3/8 | 2-1/2 | C6-1/2 | 18393 | 18394 | 18395 | 18396 | 18397 |
| 5/8 | 3/8 | 2-5/8 | C6-5/8 | 18398 | 18399 | 18400 | 18401 | 18402 |
| 3/4 | 1/2 | 2-3/4 | C6-3/4 | 18403 | 18404 | 18405 | 18406 | 18407 |
| 7/8 | 1/2 | 3 | C6-7/8 | 11565 | 11567 | 11569 | N/A | N/A |
| 1 | 1/2 | 3 | C6-1 | 18488 | 18489 | 18490 | 18491 | 18492 |
| 1-1/4 | 3/4 | 3-3/8 | C6-1-1/4 | 10891 | 10893 | 10895 | N/A | N/A |

To order countersinks: Use the EDP # listed or add the angle to the end of the tool name (i.e. C6-1/4-90).

SPEED & FEED INFORMATION

Carbide Drills

SERIES: HDR, IDR, JDR, LDR, HDRNC

| MATERIAL | ISO | CARBIDE SFM | HSSCO SFM | FEED RATE PER TOOTH (IPR) | | | |
|----------------------------|-----|-------------|-----------|---------------------------|--------|--------|--------|
| | | | | 1/16" | 1/8" | 1/4" | 1/2" |
| Stainless Steels-Soft | M | 80-300 | 20-40 | 0.0005 | 0.0005 | 0.0020 | 0.0040 |
| Stainless Steels-Hard (PH) | M | 40-100 | 15-25 | 0.0005 | 0.0005 | 0.0010 | 0.0015 |
| Nickel Base Alloys | S | 75-200 | 15-25 | 0.0005 | 0.0006 | 0.0010 | 0.0015 |
| Inconel/Monel/Hastelloy | S | 75-200 | 15-25 | 0.0005 | 0.0005 | 0.0010 | 0.0015 |
| Titanium-Soft | S | 80-350 | 20-25 | 0.0005 | 0.0020 | 0.0040 | 0.0050 |
| Titanium-Hard | S | 40-100 | 20-25 | 0.0005 | 0.0008 | 0.0020 | 0.0040 |
| Low Carbon Steels | P | 150-300 | 75-130 | 0.0005 | 0.0010 | 0.0020 | 0.0040 |
| Die Steels | P | 60-130 | 30-45 | 0.0005 | 0.0005 | 0.0020 | 0.0040 |
| Hardened Steels > HRc 50 | H | 25-75 | - | 0.0005 | 0.0010 | 0.0020 | 0.0030 |
| Cast Iron | K | 100-300 | 60-110 | 0.0010 | 0.0020 | 0.0030 | 0.0050 |
| Malleable Iron | K | 65-200 | 40-80 | 0.0010 | 0.0020 | 0.0030 | 0.0050 |
| Aluminium Alloys | N | 100-400 | 150-250 | 0.0010 | 0.0020 | 0.0030 | 0.0050 |
| Brass & Bronze | N | 150-300 | 100-150 | 0.0005 | 0.0010 | 0.0020 | 0.0040 |
| Copper | N | 150-300 | 75-150 | 0.0010 | 0.0030 | 0.0050 | 0.0060 |
| Magnesium | N | 300-600 | 200-350 | 0.0015 | 0.0030 | 0.0050 | 0.0080 |
| Plastics | N | 150-450 | 70-150 | 0.0015 | 0.0030 | 0.0040 | 0.0060 |

Countersinks

| MATERIAL | ISO | HSS SFM | COUNTERSINK TYPE | |
|-----------------------------------|-----|---------|-----------------------------------|-------------|
| | | | M42 8% COBALT WITH TiN SFM | CARBIDE SFM |
| Stainless Steels - Free Machining | M | 30-80 | 40-100 | 80-125 |
| Stainless Steels - Others | M | 15-50 | 20-65 | 50-75 |
| Inconels/Monels | S | 30-50 | 40-65 | 50-75 |
| Titaniums (6Al4V) | S | 50-60 | 60-75 | 60-90 |
| Steels Annealed | P | 40-50 | 50-65 | 50-80 |
| Steels HRc 18-24 | P | 30-40 | 40-50 | 40-60 |
| Steels HRc 25-37 | P | 25-35 | 30-45 | 35-55 |
| Mild Steels | P | 70-100 | 85-125 | 80-170 |
| Cast Iron | K | 75-125 | 95-150 | 125-225 |
| Malleable Iron | K | 80-90 | 100-115 | 90-150 |
| Aluminums Alloys | N | 150-250 | 180-300 | 300-500 |
| Brass (Bronze) | N | 75-125 | 95-150 | 150-250 |
| Magnesium | N | 125-250 | 150-300 | 250-400 |
| Plastics | N | 100-250 | 125-300 | 250-400 |

► Multiple flute countersinks are designed for increased feed rates. A controlled feed rate will result in better surface finish.

► All Melin countersinks are manufactured on CNC grinders to ensure consistent and accurate flute spacing. Carbide countersinks should be used in rigid tool holders to maximize tool life.

All technical data provided are suggested starting points. They may be increased or decreased depending on machine condition, depth of cut, finish required, coolant, etc. Call our TECHNICAL SERVICE TEAM with questions.

SPEED & FEED INFORMATION

Calculations

End mill speed & feed formulas are the various individual equations that determine the proper overall machining setup or more specifically the speed of the cutting tool and the rate which it is fed into the work piece. Each individual formula is distinct in what it determines but coordinates with the others to ensure successful cutting tool application. You can visit the TECHNICAL section on www.melintool.com for more information.

INCH

$$\text{RPM} = \frac{\text{Revolutions Per Minute}}{3.82 \times \text{SFM} / \text{Tool Dia}}$$

$$\text{SFM} = \frac{\text{Surface Foot Per Minute}}{.262 \times \text{RPM} \times \text{Tool Dia}}$$

$$\text{CPT or IPT} = \frac{\text{Chip-Load Per Tooth}}{\text{IPM} / \text{RPM} / \text{No. Of Flutes}}$$

$$\text{IPM} = \frac{\text{Inches Per Minute}}{\text{CPT} \times \text{RPM} \times \text{No. Of Flutes}}$$

$$\text{MRRCI} = \frac{\text{Metal Removal Rate Cubic Inches}}{\text{IPM} \times \text{Axial Doc} \times \text{Radial Woc}}$$

$$\text{IPR} = \frac{\text{Inches Per Revolution}}{\text{IPM} / \text{RPM}}$$

METRIC

$$\text{RPM} = \frac{\text{Revolutions Per Minute}}{1000 \times \text{M/MIN} / (3.14 \times \text{D})}$$

$$\text{M/MIN} = \frac{\text{Meters Per Minute}}{(3.14 \times \text{D} \times \text{RPM}) / 1000}$$

$$\text{Fz OR CPT} = \frac{\text{Chip-Load Per Tooth}}{\text{Feedrate (mm) per MIN} / (\text{Z} \times \text{RPM})}$$

$$\text{VF OR FPM} = \frac{\text{Feedrate (mm) Per Minute}}{\text{Feedrate (mm) per Tooth} \times \text{Z} \times \text{RPM}}$$

D = Cutter Dia.
Z = No. Of Teeth.

EQUIVALENTS & CONVERSIONS:

ABBREVIATIONS

| ABBREVIATIONS | |
|---------------|----------------------------|
| RPM | Revolutions Per Minute |
| SFM | Surface Feet Per Minute |
| CPT | Chip Load Per Tooth |
| IPM | Inches Per Minute |
| V_f | Millimeters Per Minute |
| ae | Radial Width of Cut |
| ap | Axial Depth of Cut |
| Vc | Surface Meters Per Minute |
| Fz | Metric Chip Load Per Tooth |

$$N, n \text{ or } \text{Min}^{-1} = \text{RPM}$$

$$Vc \text{ or } \text{M/MIN} = \text{SFM}$$

$$Fz \text{ or } \text{mm/TOOTH} = \text{CPT}$$

$$V_f \text{ or } \text{mm/MIN} = \text{IPM}$$

$$\text{SFM} / 3.281 = \text{M/MIN}$$

$$\text{M/MIN} \times 3.281 = \text{SFM}$$

$$\text{mm/MIN} / 25.4 = \text{IPM}$$

$$\text{mm/TOOTH} / 25.4 = \text{CPT}$$



IMPERIAL METRIC

$$\text{Inch} \times 25.4 = \text{Millimeter}$$

$$\text{Millimeter} \times .03937 = \text{Inch}$$

Countersinks

Nose Diameter for Pre-Setting CNC Precision Countersinks

| SIZE | NC POINT DIAMETER | | | | | |
|-------|-------------------|-------|-------|-------|-------|-------|
| | 60° | 82° | 90° | 100° | 110° | 120° |
| 0.188 | 0.058 | 0.032 | 0.032 | 0.032 | 0.032 | 0.032 |
| 0.250 | 0.078 | 0.046 | 0.046 | 0.046 | 0.046 | 0.046 |
| 0.313 | 0.080 | 0.047 | 0.047 | 0.047 | 0.047 | 0.047 |
| 0.375 | 0.125 | 0.078 | 0.078 | 0.078 | 0.062 | 0.062 |
| 0.438 | 0.140 | 0.096 | 0.096 | 0.096 | 0.070 | 0.070 |
| 0.500 | 0.156 | 0.109 | 0.109 | 0.109 | 0.078 | 0.078 |
| 0.625 | 0.203 | 0.125 | 0.125 | 0.125 | 0.109 | 0.109 |
| 0.750 | 0.250 | 0.156 | 0.156 | 0.156 | 0.125 | 0.125 |
| 0.875 | 0.281 | 0.172 | 0.172 | 0.172 | 0.140 | 0.140 |
| 1.000 | 0.328 | 0.203 | 0.203 | 0.203 | 0.171 | 0.171 |

Carbide Burs

SERIES: Carbide Burs

| Bur Diameter | RPM |
|---|---------------|
| 1/8 Solid Carbide | 45,000-50,000 |
| 3/16 Solid Carbide | 35,000-40,000 |
| 3/16 Carbide Head Brazed to 1/8 Steel Shank | 30,000-35,000 |
| 1/4 Solid Carbide | 30,000-35,000 |
| Carbide Head Brazed to 1/8 Steel Shank | 25,000-30,000 |
| 5/16 Carbide Head Brazed to 1/4 Steel Shank | 25,000-30,000 |
| 3/8 Carbide Head Brazed to 1/4 Steel Shank | 25,000-30,000 |
| 7/16 Carbide Head Brazed to 1/4 Steel Shank | 20,000-25,000 |
| 1/2 Carbide Head Brazed to 1/4 Steel Shank | 20,000-25,000 |
| 5/8 Carbide Head Brazed to 1/4 Steel Shank | 15,000-20,000 |
| 3/4 Carbide Head Brazed to 1/4 Steel Shank | 15,000-20,000 |
| 1 Carbide Head Brazed to 1/4 Steel Shank | 12,000-18,000 |

All technical data provided are suggested starting points. They may be increased or decreased depending on machine condition, depth of cut, finish required, coolant, etc. Call our TECHNICAL SERVICE TEAM with questions.