

## TAPPING SPEED GUIDE

MATERIALS			SPEED FEET PER MINUTE	MATERIALS			SPEED FEET PER MINUTE
Aluminum Alloys			90-100	(Steel, Cont.) Carbon Steel, Plain	Annealed	40-80	
Brass			60-100		Tempered	15-40	
Bronze			40-60	Cast, Carbon	Annealed	40-50	
Copper			40-60		Tempered	30	
High Temperature Alloys			Cobalt Base	5-10	Cast, Corrosion Resistant, Heat Resistant, Low Alloy	Annealed	20-30
			Iron Base	10-15		as Cast	20-25
			Nickel Base	5-10		Annealed	30-45
Iron	Ductile	Annealed	60	Precipitation Hardening, Stainless	Tempered	15-25	
		as Cast	30		Treated	10-15	
		Tempered	15-20		Annealed	15-45	
	Gray,	Annealed	80		Tempered	15-25	
		As Cast	35-60		Annealed	45-75	
	Malleable	Heat Treated	25-50		Tool Steels, High Speed	Annealed	15-25
Magnesium Alloys			Annealed	175	Free Machining, Water Hardening	Annealed	50
Manganese				20	Ultra High Strength Steels	Annealed	35
Molybdenum Alloys			Stress Relieved	50		Normalized	20
Monel			Annealed	20		Tempered	3-7
Nickel Alloys			Annealed	25	Maraging Steels	Annealed	20-15
Plastics, Reinforced				25		Maraged	5-10
			Thermoplastics	50	Tantalum Alloys, Stress Relieved		3
			Thermosetting Plastics	50	Titanium Alloys, Commercial Pure, Alpha & Alpha Beta Alloys,	Annealed	40-60
Steels, Alloys, Annealed or Cold Drawn				40-60		Annealed	10-25
			Quenched & Tempered	15-35	Tungsten Alloys, Pressed & Sintered		50
			Armor Plate	10	Zinc Alloys	Die Cast	150

## CONVERSION TABLE, SURFACE FEET PER MINUTE TO REVOLUTIONS PER MINUTE

SPEED FEET PER MINUTE	20	25	30	40	50	60	70	80	90	100	110	120	130	140	150
TAP SIZE	REVOLUTIONS PER MINUTE														
0	1273	1592	1910	2546	3183	3820	4456	5093	5730	6366	7003	7639	8276	8913	9549
1	1047	1308	1570	2093	2617	3140	3663	4186	4710	5233	5756	6279	6808	7326	7849
2	888	1110	1333	1777	2221	2665	3109	3554	3999	4442	4886	5330	5774	6218	6662
3	772	964	1157	1543	1929	2315	2701	3086	3472	3858	4244	4629	5015	5401	5787
4	682	853	1023	1364	1705	2046	2387	2728	3069	3411	3751	4092	4434	4775	5116
5	611	764	917	1222	1528	1833	2139	2445	2750	3056	3361	3667	3973	4278	4584
6	553	691	829	1106	1382	1658	1934	2211	2487	2764	3040	3316	3592	3869	4145
8	466	583	699	932	1165	1398	1631	1864	2097	2330	2563	2796	3029	3262	3495
10	401	502	603	804	1005	1205	1406	1607	1808	2009	2210	2411	2612	2813	3014
12	354	442	531	707	884	1061	1238	1415	1592	1769	1945	2122	2300	2476	2653
1/4	306	382	458	611	764	917	1070	1222	1375	1528	1681	1833	1986	2139	2292
5/16	245	306	367	489	611	733	856	978	1100	1222	1345	1467	1589	1711	1833
3/8	204	255	306	407	509	611	713	815	917	1019	1120	1222	1324	1426	1528
7/16	175	219	262	349	437	524	611	698	786	873	960	1048	1135	1222	1310
1/2	153	191	229	306	382	458	535	611	688	764	840	917	993	1070	1146
9/16	137	172	206	275	344	412	481	550	619	687	756	825	893	963	1031
5/8	122	153	183	244	306	367	428	489	550	611	672	733	794	856	917
3/4	102	128	153	203	255	306	357	407	458	509	560	611	662	713	764
7/8	87	109	131	175	218	262	306	350	392	437	480	524	568	611	655
1	76	96	115	153	191	230	268	306	344	382	420	458	497	535	573

## SPIRAL POINT TAPS FRACTIONAL SIZES

LIST 102C

Spiral Point Plug  
Spiral Point Bottom



TAP SIZE	SERIES DESIG.	NO. OF FLUTES	STYLE	EDP NUMBER					
				L-1	H-1	H-2	H-3	H-4	H-5
1/4 - 20	NC	2	SPPT PLUG	32592	32512	32522	32532		32552
1/4 - 20	NC	2	SPPT BOTT				32533		
1/4 - 20	NC	3	SPPT PLUG		32612	32622	32632		32652
1/4 - 20	NC	3	SPPT BOTT				32633		
1/4 - 28	NF	2	SPPT PLUG		32712	32722	32732	32742	
1/4 - 28	NF	2	SPPT BOTT				32733		
1/4 - 28	NF	3	SPPT PLUG		32812	32822	32832	32842	
1/4 - 28	NF	3	SPPT BOTT				32833		
5/16 - 18	NC	2	SPPT PLUG	32992	32912	32922	32932		32952
5/16 - 18	NC	2	SPPT BOTT				32933		
5/16 - 18	NC	3	SPPT PLUG		33012	33022	33032		33052
5/16 - 18	NC	3	SPPT BOTT				33033		
5/16 - 24	NF	2	SPPT PLUG		33112	33122	33132	33142	
5/16 - 24	NF	2	SPPT BOTT				33133		
5/16 - 24	NF	3	SPPT PLUG		33212	33222	33232	33242	
5/16 - 24	NF	3	SPPT BOTT				33233		
3/8 - 16	NC	3	SPPT PLUG	33392	33312	33322	33332		33352
3/8 - 16	NC	3	SPPT BOTT				33333		
3/8 - 24	NF	3	SPPT PLUG		33412	33422	33432	33442	
3/8 - 24	NF	3	SPPT BOTT				33433		
7/16 - 14	NC	3	SPPT PLUG	33592	33512	33522	33532		33552
7/16 - 14	NC	3	SPPT BOTT				33533		
7/16 - 20	NF	3	SPPT PLUG		33612	33622	33632		33652
7/16 - 20	NF	3	SPPT BOTT				33633		
1/2 - 13	NC	3	SPPT PLUG	33792	33712	33722	33732		33752
1/2 - 13	NC	3	SPPT BOTT				33733		
1/2 - 20	NF	3	SPPT PLUG		33812	33822	33832		33852
1/2 - 20	NF	3	SPPT BOTT				33833		
9/16 - 12	NC	3	SPPT PLUG		33912	33922	33932		33952
9/16 - 12	NC	3	SPPT BOTT				33933		
9/16 - 18	NF	3	SPPT PLUG		34012	34022	34032		34052
9/16 - 18	NF	3	SPPT BOTT				34033		
5/8 - 11	NC	3	SPPT PLUG		34112	34122	34132		34152
5/8 - 11	NC	3	SPPT BOTT				34133		
5/8 - 18	NF	3	SPPT PLUG		34212	34222	34232		34252
5/8 - 18	NF	3	SPPT BOTT				34233		
11/16 - 11	NS	3	SPPT PLUG				34332		
11/16 - 11	NS	3	SPPT BOTT				34333		
11/16 - 16	NS	3	SPPT PLUG				34432		
11/16 - 16	NS	3	SPPT BOTT				34433		
3/4 - 10	NC	3	SPPT PLUG		34512	34522	34532		34552
3/4 - 10	NC	3	SPPT BOTT				34533		
3/4 - 16	NF	3	SPPT PLUG		34612	34622	34632		34652
3/4 - 16	NF	3	SPPT BOTT				34633		
7/8 - 9	NC	3	SPPT PLUG					34852	
7/8 - 9	NC	4	SPPT PLUG					34842	
7/8 - 14	NF	3	SPPT PLUG					34952	
7/8 - 14	NF	4	SPPT PLUG					34942	
1 - 8	NC	3	SPPT PLUG					35052	
1 - 8	NC	4	SPPT PLUG					35042	
1 - 12	NF	4	SPPT PLUG					35142	
1 - 14	NS	4	SPPT PLUG					35242	






## TAP DRILL SIZES AND PERCENTAGE OF THREADS

TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD	TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD	TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD
NOM. SIZE	TPI				NOM. SIZE	TPI				NOM. SIZE	TPI			
0	80	#56	.0465	83	1/4	20	13/64	.2031	72	5/8	18	9/16	.5625	87
		3/64	.0469	81			#6	.2040	71			0.5687	.5687	78
1	64	#54	.0550	89	1/4	28	#5	.2055	69	5/8	20	37/64	.5781	72
		#53	.0595	67			#3	.2130	80			37/64	.5781	87
1	72	#53	.0595	75	1/4	32	7/32	.2188	67	5/8	24	0.5828	.5828	78
		1/16	.0625	58			7/32	.2188	77			5/8	28	19/32
2	56	#51	.0670	82	1/4	36	#2	.2210	71	5/8	32	19/32	.5938	77
		#50	.0700	69			#2	.2210	80			19/32	.5938	87
2	64	#49	.0730	56	5/16	18	F	.2570	77	11/16	12	39/64	.6094	72
		#50	.0700	79			G	.2610	71			5/8	16	5/8
3	48	#48	.0760	85	5/16	20	F	.2570	85	11/16	20	41/64	.6406	72
		5/64	.0781	77			G	.2610	79			11/16	24	41/64
3	56	#47	.0785	76	5/16	24	H	.2660	72	11/16	28	21/32	.6562	67
		#46	.0810	67			H	.2660	86			11/16	32	21/32
3	40	#45	.0820	63	5/16	28	I	.2720	75	3/4	10	41/64	.6406	84
		#48	.0810	78			J	.2770	66			21/32	.6562	72
4	40	#44	.0860	80	5/16	32	J	.2770	77	3/4	12	21/32	.6562	87
		#43	.0890	71			K	.2810	68			43/64	.6719	72
4	48	#42	.0935	57	5/16	36	9/32	.2812	67	3/4	16	11/16	.6875	77
		3/32	.0938	56			K	.2810	78			3/4	20	45/64
4	48	#43	.0890	85	3/8	16	7.25mm	.2854	75	3/4	28	23/32	.7188	67
		#42	.0935	68			5/16	.3125	77			3/4	32	23/32
5	40	#41	.0960	59	3/8	20	O	.3160	73	13/16	12	47/64	.7344	72
		#40	.0980	83			P	.3230	80			13/16	16	3/4
5	44	#39	.0995	79	3/8	24	Q	.3320	66	13/16	20	49/64	.7656	72
		#38	.1015	72			Q	.3320	79			13/16	28	25/32
5	32	#37	.1040	65	3/8	28	R	.3390	67	13/16	32	25/32	.7812	77
		#38	.1015	80			11/32	.3438	67			7/8	9	49/64
6	40	#37	.1040	71	3/8	32	11/32	.3438	77	7/8	12	25/32	.7812	87
		#36	.1065	63			11/32	.3438	77			7/8	14	51/64
6	48	#37	.1040	84	3/8	36	S	.3480	75	7/8	14	51/64	.7969	84
		#36	.1065	78			S	.3480	75			0.8024	.8024	78
6	40	7/64	.1094	70	7/16	14	T	.3580	86	7/8	16	13/16	.8125	77
		#35	.1100	69			23/64	.3594	84			7/8	20	53/64
6	48	#34	.1110	67	7/16	16	3/8	.3750	77	7/8	28	27/32	.8438	67
		#33	.1130	77			V	.3770	75			7/8	32	27/32
8	32	#34	.1110	83	7/16	20	W	.3860	79	7/8	32	27/32	.8438	87
		#33	.1130	77			25/64	.3906	72			27/32	.8438	87
8	36	#32	.1160	68	7/16	28	Y	.4040	72	15/16	12	27/32	.8438	87
		#29	.1360	69			Y	.4040	83			55/64	.8594	72
8	48	#29	.1360	78	7/16	32	13/32	.4062	77	15/16	16	7/8	.8750	77
		#28	.1405	65			Z	.4130	80			15/16	20	57/64
10	24	9/64	.1406	65	1/2	12	27/64	.4219	72	15/16	28	29/32	.9062	67
		#27	.1440	85			27/64	.4219	78			15/16	32	29/32
10	32	#26	.1470	79	1/2	13	7/16	.4375	77	1	8	55/64	.8594	87
		#25	.1495	75			29/64	.4531	72			7/8	.8750	77
10	40	#24	.1520	70	1/2	16	15/32	.4688	67	1	12	29/32	.9062	87
		#23	.1540	66			15/32	.4688	77			59/64	.9219	72
10	48	5/32	.1562	83	1/2	18	15/32	.4688	87	1	14	59/64	.9219	84
		#22	.1570	81			31/64	.4844	72			0.9274	.9274	78
12	24	#21	.1590	76	9/16	12	1/2	.5000	77	1	16	15/16	.9375	77
		#20	.1610	71			0.5062	.5062	69			1	20	61/64
12	32	11/64	.1719	82	9/16	16	1/2	.5000	87	1	28	31/32	.9688	67
		#17	.1730	79			0.5062	.5062	78			1	32	31/32
12	40	#16	.1770	72	9/16	20	33/64	.5156	72	1 1/16	8	59/64	.9219	87
		#15	.1800	67			33/64	.5156	87			0.9274	.9274	83
12	48	#16	.1770	84	9/16	24	0.5203	.5203	78	1 1/16	12	15/16	.9375	77
		#15	.1800	78			17/32	.5312	67			31/32	.9688	87
12	56	#14	.1820	73	9/16	28	0.5263	.5263	78	1 1/16	16	63/64	.9844	72
		#13	.1850	67			17/32	.5312	77			1	1.0000	77
12	64	#14	.1820	84	9/16	32	17/32	.5312	77	1 1/16	18	1	1.0000	87
		#13	.1850	76			5/8	11	17/32			.5312	79	1 1/16
1/4	20	3/16	.1875	70	5/8	12	35/64	.5469	72	1 1/16	20	11/64	1.0156	72
		#12	.1890	67			9/16	5.625	77					
1/4	28	#9	.1960	83	5/8	16	0.5687	.5687	69	1 1/16	20	11/64	1.0156	72
		#8	.1990	79			9/16	5.625	77					
1/4	36	#7	.2010	75	5/8	16	0.5687	.5687	69	1 1/16	20	11/64	1.0156	72

## STANDARD TAP DIMENSIONS, GROUND THREAD

### General Dimensions



NOMINAL DIAMETER RANGE - INCHES		MACHINE SCREW SIZE NO.	NOMINAL FRACTIONAL DIAMETER INCHES	NOMINAL METRIC DIAMETER MILLIMETER	STYLE*	TAP DIMENSIONS - INCHES				
						O/A LENGTH A	THD. LGTH. B	SQ. LGTH. C	SHANK DIA. D	SIZE OF SQ. E
OVER	TO (INCL.)									
.052	.065	0	1/16	M1.6	1	1 5/8	5/16	3/16	.141	.110
.065	.078	1		M1.8	1	1 11/16	3/8	3/16	.141	.110
.078	.091	2		M2, M2.2	1	1 3/4	7/16	3/16	.141	.110
.091	.104	3	3/32	M2.5	1	1 13/16	1/2	3/16	.141	.110
.104	.117	4			1	1 7/8	9/16	3/16	.141	.110
.117	.130	5	1/8	M3, M3.15	1	1 15/16	5/8	3/16	.141	.110
.130	.145	6		M3.5	1	2	11/16	3/16	.141	.110
.145	.171	8	5/32	M4	1	2 1/8	3/4	1/4	.168	.131
.171	.197	10	3/16	M4.5, M5	1	2 3/8	7/8	1/4	.194	.152
.197	.223	12	7/32		1	2 3/8	15/16	9/32	.220	.165
.223	.260	14	1/4	M6, M6.3	2	2 1/2	1	5/16	.255	.191
.260	.323		5/16	M7, M8	2	2 23/32	1 1/8	3/8	.318	.238
.323	.395		3/8	M10	2	2 15/16	1 1/4	7/16	.381	.286
.395	.448		7/16		3	3 5/32	1 7/16	13/32	.323	.242
.448	.510		1/2	M12, M12.5	3	3 3/8	1 21/32	7/16	.367	.275
.510	.573		9/16	M14	3	3 19/32	1 21/32	1/2	.429	.322
.573	.635		5/8	M16	3	3 13/16	1 13/16	9/16	.480	.360
.635	.709		11/16	M18	3	4 1/32	1 13/16	5/8	.542	.406
.709	.760		3/4		3	4 1/4	2	11/16	.590	.442
.760	.823		13/16	M20	3	4 15/32	2	11/16	.652	.489
.823	.885		7/8	M22	3	4 11/16	2 7/32	3/4	.697	.523
.885	.948		15/16	M24	3	4 29/32	2 7/32	3/4	.760	.570
.948	1.010		1	M25	3	5 1/8	2 1/2	13/16	.800	.600
1.010	1.073		1 1/16	M27	3	5 1/8	2 1/2	7/8	.896	.672
1.073	1.135		1 1/8		3	5 7/16	2 9/16	7/8	.896	.672
1.135	1.198		1 3/16	M30	3	5 7/16	2 9/16	1	1.021	.766
1.198	1.260		1 1/4		3	5 3/4	2 9/16	1	1.021	.766
1.260	1.323		1 5/16	M33	3	5 3/4	2 9/16	1 1/16	1.108	.831
1.323	1.385		1 3/8		3	6 1/16	3	1 1/16	1.108	.831
1.385	1.448		1 7/16	M36	3	6 1/16	3	1 1/8	1.233	.925
1.448	1.510		1 1/2		3	6 3/8	3	1 1/8	1.233	.925
1.510	1.635		1 5/8	M39	3	6 11/16	3 3/16	1 1/8	1.305	.979
1.635	1.760		1 3/4	M42	3	7	3 3/16	1 1/4	1.430	1.072
1.760	1.885		1 7/8		3	7 5/16	3 9/16	1 1/4	1.519	1.139
1.885	2.010		2	M48	3	7 5/8	3 9/16	1 3/8	1.644	1.233
2.010	2.135		2 1/8		3	8	3 9/16	1 3/8	1.769	1.327
2.135	2.260		2 1/4	M56	3	8 1/4	3 9/16	1 7/16	1.894	1.420
2.260	2.385		2 3/8		3	8 1/2	4	1 7/16	2.019	1.514
2.385	2.510		2 1/2		3	8 3/4	4	1 1/2	2.100	1.575
2.510	2.635		2 5/8	M64	3	8 3/4	4	1 1/2	2.225	1.669
2.635	2.760		2 3/4		3	9 1/4	4	1 9/16	2.350	1.762
2.760	2.885		2 7/8	M72	3	9 1/4	4	1 9/16	2.475	1.856
2.885	3.010		3		3	9 3/4	4 9/16	1 5/8	2.543	1.907
3.010	3.135		3 1/8		3	9 3/4	4 9/16	1 5/8	2.668	2.001
3.135	3.260		3 1/4	M80	3	10	4 9/16	1 3/4	2.793	2.095

\*Styles shown are for Ground Thread Taps.