

TAPPING SPEED GUIDE

MATERIALS			SPEED FEET PER MINUTE	MATERIALS			SPEED FEET PER MINUTE
Aluminum Alloys			90-100	(Steel, Cont.) Carbon Steel, Plain	Annealed	40-80	
Brass			60-100		Tempered	15-40	
Bronze			40-60	Cast, Carbon	Annealed	40-50	
Copper			40-60		Tempered	30	
High Temperature Alloys	Cobalt Base		5-10	Cast, Corrosion Resistant, Heat Resistant, Low Alloy	Annealed	20-30	
		Iron Base	10-15		as Cast	20-25	
		Nickel Base	5-10		Annealed	30-45	
Iron	Ductile	Annealed	60	Precipitation Hardening, Stainless	Tempered	15-25	
		as Cast	30		Treated	10-15	
		Tempered	15-20		Annealed	15-45	
	Gray,	Annealed	80		Tempered	15-25	
		As Cast	35-60		Annealed	45-75	
	Malleable		60	Tool Steels, High Speed	Annealed	15-25	
		Heat Treated	25-50		Water Hardening	Annealed	50
Magnesium Alloys		Annealed	175	Ultra High Strength Steels	Annealed	35	
Manganese			20		Normalized	20	
Molybdenum Alloys		Stress Relieved	50		Tempered	3-7	
Monel		Annealed	20	Maraging Steels	Annealed	20-15	
Nickel Alloys		Annealed	25		Maraged	5-10	
Plastics,	Reinforced		25	Tantalum Alloys, Stress Relieved		3	
	Thermoplastics		50	Titanium Alloys, Commercial Pure,	Annealed	40-60	
	Thermosetting Plastics		50	Alpha & Alpha Beta Alloys,	Annealed	10-25	
Steels,	Alloys, Annealed or Cold Drawn		40-60	Tungsten Alloys, Pressed & Sintered		50	
	Quenched & Tempered		15-35	Zinc Alloys	Die Cast	150	
	Armor Plate		10				

CONVERSION TABLE, SURFACE FEET PER MINUTE TO REVOLUTIONS PER MINUTE

SPEED FEET PER MINUTE	20	25	30	40	50	60	70	80	90	100	110	120	130	140	150
TAP SIZE	REVOLUTIONS PER MINUTE														
0	1273	1592	1910	2546	3183	3820	4456	5093	5730	6366	7003	7639	8276	8913	9549
1	1047	1308	1570	2093	2617	3140	3663	4186	4710	5233	5756	6279	6808	7326	7849
2	888	1110	1333	1777	2221	2665	3109	3554	3999	4442	4886	5330	5774	6218	6662
3	772	964	1157	1543	1929	2315	2701	3086	3472	3858	4244	4629	5015	5401	5787
4	682	853	1023	1364	1705	2046	2387	2728	3069	3411	3751	4092	4434	4775	5116
5	611	764	917	1222	1528	1833	2139	2445	2750	3056	3361	3667	3973	4278	4584
6	553	691	829	1106	1382	1658	1934	2211	2487	2764	3040	3316	3592	3869	4145
8	466	583	699	932	1165	1398	1631	1864	2097	2330	2563	2796	3029	3262	3495
10	401	502	603	804	1005	1205	1406	1607	1808	2009	2210	2411	2612	2813	3014
12	354	442	531	707	884	1061	1238	1415	1592	1769	1945	2122	2300	2476	2653
1/4	306	382	458	611	764	917	1070	1222	1375	1528	1681	1833	1986	2139	2292
5/16	245	306	367	489	611	733	856	978	1100	1222	1345	1467	1589	1711	1833
3/8	204	255	306	407	509	611	713	815	917	1019	1120	1222	1324	1426	1528
7/16	175	219	262	349	437	524	611	698	786	873	960	1048	1135	1222	1310
1/2	153	191	229	306	382	458	535	611	688	764	840	917	993	1070	1146
9/16	137	172	206	275	344	412	481	550	619	687	756	825	893	963	1031
5/8	122	153	183	244	306	367	428	489	550	611	672	733	794	856	917
3/4	102	128	153	203	255	306	357	407	458	509	560	611	662	713	764
7/8	87	109	131	175	218	262	306	350	392	437	480	524	568	611	655
1	76	96	115	153	191	230	268	306	344	382	420	458	497	535	573

SPIRAL POINT TAPS MACHINE SCREW SIZES

LIST 106C

**Spiral Point Plug
 Spiral Point Bottom**



TAP SIZE	SERIES DESIGN.	NO. OF FLUTES	STYLE	EDP NUMBER		
				H-1	H-2	H-3
0 - 80	NF	2	SPPT PLUG	14112	14122	
0 - 80	NF	2	SPPT BOTT	14113	14123	
1 - 64	NC	2	SPPT PLUG	14212	14222	
1 - 64	NC	2	SPPT BOTT	14213	14223	
1 - 72	NF	2	SPPT PLUG	14312	14322	
1 - 72	NF	2	SPPT BOTT	14313	14323	
2 - 56	NC	2	SPPT PLUG	14412	14422	
2 - 56	NC	2	SPPT BOTT	14413	14423	
2 - 64	NF	2	SPPT PLUG	14512	14522	
2 - 64	NF	2	SPPT BOTT	14513	14523	
3 - 48	NC	2	SPPT PLUG	14612	14622	
3 - 48	NC	2	SPPT BOTT	14613	14623	
3 - 56	NF	2	SPPT PLUG	14712	14722	
3 - 56	NF	2	SPPT BOTT	14713	14723	
4 - 40	NC	2	SPPT PLUG	14912	14922	
4 - 40	NC	2	SPPT BOTT	14913	14923	
4 - 48	NF	2	SPPT PLUG	15012	15022	
4 - 48	NF	2	SPPT BOTT	15013	15023	
4 - 36	NS	2	SPPT PLUG	14812	14822	
4 - 36	NS	2	SPPT BOTT	14813	14823	
5 - 40	NC	2	SPPT PLUG	15112	15122	
5 - 40	NC	2	SPPT BOTT	15113	15123	
5 - 44	NF	2	SPPT PLUG	15212	15222	
5 - 44	NF	2	SPPT BOTT	15213	15223	
6 - 32	NC	2	SPPT PLUG	15312	15322	15332
6 - 32	NC	2	SPPT BOTT	15313	15323	15333
6 - 40	NF	2	SPPT PLUG	15412	15422	
6 - 40	NF	2	SPPT BOTT	15413	15423	
8 - 32	NC	2	SPPT PLUG	15512	15522	15532
8 - 32	NC	2	SPPT BOTT	15513	15523	15533
8 - 36	NF	2	SPPT PLUG	15612	15622	15632
8 - 36	NF	2	SPPT BOTT	15613	15623	15633
10 - 24	NC	2	SPPT PLUG	15712	15722	15732
10 - 24	NC	2	SPPT BOTT	15713	15723	15733
10 - 32	NF	2	SPPT PLUG	15812	15822	15832
10 - 32	NF	2	SPPT BOTT	15813	15823	15833
12 - 24	NC	2	SPPT PLUG	15912		15932
12 - 24	NC	2	SPPT BOTT	15913		15933
12 - 28	NF	2	SPPT PLUG	16012		16032
12 - 28	NF	2	SPPT BOTT	16013		16033
14 - 20	NS	2	SPPT PLUG			16132
14 - 24	NS	2	SPPT PLUG			16232




TAP DRILL SIZES AND PERCENTAGE OF THREADS


TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD	TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD	TAP		TAP DRILL	DECIM. EQUIV.	THEOR. % OF THREAD
NOM. SIZE	TPI				NOM. SIZE	TPI				NOM. SIZE	TPI			
0	80	#56	.0465	83	1/4	20	13/64	.2031	72	5/8	18	9/16	.5625	87
		3/64	.0469	81			#6	.2040	71			0.5687	.5687	78
1	64	#54	.0550	89	1/4	28	#5	.2055	69	5/8	20	37/64	.5781	72
		#53	.0595	67			#3	.2130	80			37/64	.5781	87
1	72	#53	.0595	75	1/4	32	7/32	.2188	67	5/8	24	0.5828	.5828	78
		1/16	.0625	58			7/32	.2188	77			5/8	28	19/32
2	56	#51	.0670	82	1/4	36	#2	.2210	71	5/8	32	19/32	.5938	77
		#50	.0700	69			#2	.2210	80			19/32	.5938	87
2	64	#49	.0730	56	5/16	18	F	.2570	77	11/16	12	39/64	.6094	72
		#50	.0700	79			G	.2610	71			5/8	16	.6250
3	48	#48	.0760	85	5/16	20	F	.2570	85	11/16	20	41/64	.6406	72
		5/64	.0781	77			G	.2610	79			11/16	24	41/64
3	56	#47	.0785	76	5/16	24	H	.2660	72	11/16	28	21/32	.6562	67
		#46	.0810	67			H	.2660	86			11/16	32	21/32
3	40	#45	.0820	63	5/16	28	I	.2720	75	3/4	10	41/64	.6406	84
		#48	.0810	78			J	.2770	66			21/32	.6562	72
4	40	#44	.0860	80	5/16	32	J	.2770	77	3/4	12	21/32	.6562	87
		#43	.0890	71			K	.2810	68			43/64	.6719	72
4	48	#42	.0935	57	5/16	36	9/32	.2812	67	3/4	16	11/16	.6875	77
		3/32	.0938	56			K	.2810	78			3/4	20	45/64
4	48	#43	.0890	85	3/8	16	9/32	.2812	77	3/4	28	23/32	.7188	67
		#42	.0935	68			7.25mm	.2854	75			3/4	32	23/32
5	40	#41	.0960	59	3/8	20	O	.3160	73	13/16	12	47/64	.7344	72
		#40	.0980	83			P	.3230	80			13/16	16	3/4
5	44	#39	.0995	79	3/8	24	Q	.3320	66	13/16	20	49/64	.7656	72
		#38	.1015	72			Q	.3320	79			13/16	28	25/32
5	32	#37	.1040	65	3/8	28	R	.3390	67	13/16	32	25/32	.7812	77
		#38	.1015	80			R	.3390	78			7/8	9	49/64
6	40	#37	.1040	71	3/8	32	11/32	.3438	67	7/8	12	25/32	.7812	87
		#36	.1065	63			11/32	.3438	77			7/8	14	51/64
6	48	#37	.1040	84	3/8	36	S	.3480	67	7/8	14	51/64	.7969	84
		#36	.1065	78			S	.3480	75			0.8024	.8024	78
6	40	7/64	.1094	70	7/16	14	T	.3580	86	7/8	16	13/16	.8125	77
		#35	.1100	69			23/64	.3594	84			7/8	20	53/64
6	48	#34	.1110	67	7/16	16	3/8	.3750	77	7/8	28	27/32	.8438	67
		#33	.1130	77			V	.3770	75			7/8	32	27/32
8	32	#34	.1110	83	7/16	20	W	.3860	79	15/16	12	27/32	.8438	87
		#33	.1130	77			25/64	.3906	72			7/8	28	27/32
8	36	#32	.1160	68	7/16	28	Y	.4040	72	15/16	16	55/64	.8594	87
		#29	.1360	69			Y	.4040	83			7/8	16	.8750
10	24	#29	.1360	78	1/2	12	13/32	.4062	77	15/16	20	57/64	.8906	72
		#28	.1405	65			Z	.4130	80			15/16	28	29/32
10	32	9/64	.1406	65	1/2	13	27/64	.4219	72	15/16	32	29/32	.9062	77
		#27	.1440	85			7/16	.4375	77			1	8	55/64
10	40	#26	.1470	79	1/2	16	29/64	.4531	72	1	12	7/8	.8750	77
		#25	.1495	75			15/32	.4688	67			29/32	.9062	87
10	48	#24	.1520	70	1/2	20	15/32	.4688	77	1	14	59/64	.9219	72
		#23	.1540	66			15/32	.4688	87			59/64	.9219	84
12	24	5/32	.1562	83	9/16	12	31/64	.4844	72	1	16	0.9274	.9274	78
		#22	.1570	81			1/2	.5000	77			15/16	.9375	77
12	28	#21	.1590	76	9/16	18	0.5062	.5062	69	1	20	61/64	.9531	72
		#20	.1610	71			1/2	.5000	87			1	28	31/32
12	32	11/64	.1719	82	9/16	20	0.5062	.5062	78	1	32	31/32	.9688	77
		#17	.1730	79			33/64	.5156	72			59/64	.9219	87
12	40	#16	.1770	84	9/16	24	1/2	.5000	87	1 1/16	8	0.9274	.9274	83
		#15	.1800	67			0.5203	.5203	78			15/16	.9375	77
12	48	#16	.1770	84	9/16	28	17/32	.5312	67	1 1/16	12	31/32	.9688	87
		#15	.1800	78			0.5263	.5263	78			63/64	.9844	72
1/4	20	#14	.1820	73	9/16	32	17/32	.5312	77	1 1/16	16	1	1.0000	77
		#13	.1850	67			5/8	11	17/32			.5312	79	1 1/16
1/4	20	#12	.1890	67	5/8	12	35/64	.5469	72	1 1/16	20	11/64	1.0156	72
		#9	.1960	83			9/16	.5625	77					
		#8	.1990	79			0.5687	.5687	69					
		#7	.2010	75										

STANDARD TAP DIMENSIONS, GROUND THREAD


General Dimensions



STYLE 1



STYLE 2



STYLE 3

NOMINAL DIAMETER RANGE - INCHES		MACHINE SCREW SIZE NO.	NOMINAL FRACTIONAL DIAMETER INCHES	NOMINAL METRIC DIAMETER MILLIMETER	STYLE*	TAP DIMENSIONS - INCHES				
						O/A LENGTH A	THD. LGTH. B	SQ. LGTH. C	SHANK DIA. D	SIZE OF SQ. E
OVER	TO (INCL.)									
.052	.065	0	1/16	M1.6	1	1 5/8	5/16	3/16	.141	.110
.065	.078	1		M1.8	1	1 11/16	3/8	3/16	.141	.110
.078	.091	2		M2, M2.2	1	1 3/4	7/16	3/16	.141	.110
.091	.104	3	3/32	M2.5	1	1 13/16	1/2	3/16	.141	.110
.104	.117	4			1	1 7/8	9/16	3/16	.141	.110
.117	.130	5	1/8	M3, M3.15	1	1 15/16	5/8	3/16	.141	.110
.130	.145	6		M3.5	1	2	11/16	3/16	.141	.110
.145	.171	8	5/32	M4	1	2 1/8	3/4	1/4	.168	.131
.171	.197	10	3/16	M4.5, M5	1	2 3/8	7/8	1/4	.194	.152
.197	.223	12	7/32		1	2 3/8	15/16	9/32	.220	.165
.223	.260	14	1/4	M6, M6.3	2	2 1/2	1	5/16	.255	.191
.260	.323		5/16	M7, M8	2	2 23/32	1 1/8	3/8	.318	.238
.323	.395		3/8	M10	2	2 15/16	1 1/4	7/16	.381	.286
.395	.448		7/16		3	3 5/32	1 7/16	13/32	.323	.242
.448	.510		1/2	M12, M12.5	3	3 3/8	1 21/32	7/16	.367	.275
.510	.573		9/16	M14	3	3 19/32	1 21/32	1/2	.429	.322
.573	.635		5/8	M16	3	3 13/16	1 13/16	9/16	.480	.360
.635	.709		11/16	M18	3	4 1/32	1 13/16	5/8	.542	.406
.709	.760		3/4		3	4 1/4	2	11/16	.590	.442
.760	.823		13/16	M20	3	4 15/32	2	11/16	.652	.489
.823	.885		7/8	M22	3	4 11/16	2 7/32	3/4	.697	.523
.885	.948		15/16	M24	3	4 29/32	2 7/32	3/4	.760	.570
.948	1.010		1	M25	3	5 1/8	2 1/2	13/16	.800	.600
1.010	1.073		1 1/16	M27	3	5 1/8	2 1/2	7/8	.896	.672
1.073	1.135		1 1/8		3	5 7/16	2 9/16	7/8	.896	.672
1.135	1.198		1 3/16	M30	3	5 7/16	2 9/16	1	1.021	.766
1.198	1.260		1 1/4		3	5 3/4	2 9/16	1	1.021	.766
1.260	1.323		1 5/16	M33	3	5 3/4	2 9/16	1 1/16	1.108	.831
1.323	1.385		1 3/8		3	6 1/16	3	1 1/16	1.108	.831
1.385	1.448		1 7/16	M36	3	6 1/16	3	1 1/8	1.233	.925
1.448	1.510		1 1/2		3	6 3/8	3	1 1/8	1.233	.925
1.510	1.635		1 5/8	M39	3	6 11/16	3 3/16	1 1/8	1.305	.979
1.635	1.760		1 3/4	M42	3	7	3 3/16	1 1/4	1.430	1.072
1.760	1.885		1 7/8		3	7 5/16	3 9/16	1 1/4	1.519	1.139
1.885	2.010		2	M48	3	7 5/8	3 9/16	1 3/8	1.644	1.233
2.010	2.135		2 1/8		3	8	3 9/16	1 3/8	1.769	1.327
2.135	2.260		2 1/4	M56	3	8 1/4	3 9/16	1 7/16	1.894	1.420
2.260	2.385		2 3/8		3	8 1/2	4	1 7/16	2.019	1.514
2.385	2.510		2 1/2		3	8 3/4	4	1 1/2	2.100	1.575
2.510	2.635		2 5/8	M64	3	8 3/4	4	1 1/2	2.225	1.669
2.635	2.760		2 3/4		3	9 1/4	4	1 9/16	2.350	1.762
2.760	2.885		2 7/8	M72	3	9 1/4	4	1 9/16	2.475	1.856
2.885	3.010		3		3	9 3/4	4 9/16	1 5/8	2.543	1.907
3.010	3.135		3 1/8		3	9 3/4	4 9/16	1 5/8	2.668	2.001
3.135	3.260		3 1/4	M80	3	10	4 9/16	1 3/4	2.793	2.095

*Styles shown are for Ground Thread Taps.