



1/4" DRIVE DEEP SOCKETS, 6 POINT, METRIC

High-Polished Chrome Finish

Product Code	A		B		C		D		E		F
	Size (MM)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)		
MMD-604	4	2	15/32	9/32	3/16	3/16	1 21/32	1/8	1 9/16		
MMD-605	5	2	15/32	5/16	3/16	3/16	1 21/32	5/32	1 9/16		
MMD-605.5	5.5	2	15/32	5/16	7/32	7/32	1 21/32	7/32	1 9/16		
MMD-606	6	2	15/32	3/8	7/32	7/32	1 21/32	7/32	1 9/16		
MMD-607	7	2	15/32	13/32	1/4	1/4	1 21/32	1/4	1 9/16		
MMD-608	8	2	15/32	15/32	9/32	9/32	1 21/32	1/4	1 9/16		
MMD-609	9	2	1/2	1/2	9/32	9/32	1 21/32	5/16	-		
MMD-610	10	2	9/16	9/16	9/32	9/32	1 21/32	3/8	-		
MMD-611	11	2	19/32	19/32	3/8	3/8	1 21/32	13/32	-		
MMD-612	12	2	21/32	21/32	3/8	3/8	1 21/32	7/16	-		
MMD-613	13	2	23/32	23/32	3/8	3/8	1 21/32	15/32	-		
MMD-614	14	2	3/4	3/4	7/16	7/16	1 21/32	17/32	-		

Fed. Spec: ANSI B1 07.5

MSMD-12HRC 12 Piece 1/4" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
MMD-604	4	MMD-606	6	MMD-609	9	MMD-612	12
MMD-605	5	MMD-607	7	MMD-610	10	MMD-613	13
MMD-605.5	5.5	MMD-608	8	MMD-611	11	MMD-614	14

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.



MMD-614 MMD-606



MSMD-12HRC



1/4" DRIVE DEEP SOCKETS, 12 POINT, METRIC

High-Polished Chrome Finish

Product Code	A		B		C		D		E		F
	Size (MM)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)		
30804	4	2	15/32	9/32	3/16	3/16	1 21/32	1/8	15/16		
30805	5	2	15/32	5/16	3/16	3/16	1 21/32	5/32	15/16		
30855	5.5	2	15/32	5/16	7/32	7/32	1 21/32	7/32	15/16		
30806	6	2	15/32	3/8	7/32	7/32	1 21/32	7/32	15/16		
30807	7	2	15/32	13/32	1/4	1/4	1 21/32	1/4	15/16		
30808	8	2	15/32	15/32	9/32	9/32	1 21/32	1/4	15/16		
30809	9	2	1/2	1/2	9/32	9/32	1 21/32	5/16	-		
30810	10	2	9/16	9/16	9/32	9/32	1 21/32	3/8	-		
30811	11	2	19/32	19/32	3/8	3/8	1 21/32	13/32	-		
30812	12	2	21/32	21/32	3/8	3/8	1 21/32	7/16	-		
30813	13	2	23/32	23/32	3/8	3/8	1 21/32	15/32	-		
30814	14	2	3/4	3/4	7/16	7/16	1 21/32	17/32	-		

Fed. Spec: ANSI B1 07.5

30941 12 Piece 1/4" Drive Deep 12 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
30804	4	30806	6	30809	9	30812	12
30805	5	30807	7	30810	10	30813	13
30855	5.5	30808	8	30811	11	30814	14

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on both 6 and 12 point fasteners.



30808 30804



30941

