



3/8" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, SAE

Black Industrial Finish

Product Code	A Size (Inches)	B OAL (Inches)	C Drive End Diameter (Inches)	D Working End Diameter (Inches)	E Broach Depth (Inches)	F Bolt Clearance Depth (Inches)	G Bolt Clearance Diameter (Inches)	H Nose Length (Inches)
2-608	1/4	1 1/32	1/16	1/2	7/32	9/16	7/32	17/32
2-610	5/16	1 1/2	1 1/16	1/2	1/4	9/16	9/32	17/32
2-612	3/8	1 1/32	1 1/16	5/8	9/32	9/16	1 1/32	17/32
2-614	7/16	1 1/32	1 1/16	21/32	9/32	19/32	1 1/32	-
2-616	1/2	1 1/32	1/16	3/4	5/16	19/32	3/6	-
2-618	9/16	1 3/32	13/16	9/16	19/32	19/32	17/32	-
2-620	5/8	1 1/8	29/32	29/32	19/32	5/8	5/8	-
2-622	11/16	1 5/32	31/32	31/32	19/32	5/8	2 1/32	-
2-624	3/4	1 3/32	1 1/16	1 1/16	21/32	11/16	2 1/32	-
2-626	13/16	1 1/4	1 1/8	1 1/8	11/16	23/32	2 1/32	-
2-628	7/8	1 1/32	1 3/16	1 3/16	3/4	3/4	2 1/32	-
2-630	15/16	1 5/16	1 9/32	1 9/32	25/32	13/16	2 1/32	-
2-632	1	1 5/16	1 11/32	1 11/32	25/32	25/32	3 1/32	-

Fed. Spec: ANSI B107.2

WS-2-8 8 Piece 3/8" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)
2-610	5/16	2-618	9/16
2-612	3/8	2-620	5/8
2-614	7/16	2-622	1 1/16
2-616	1/2	2-624	3/4



WS-2-13 13 Piece 3/8" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
2-608	1/4	2-618	9/16	2-628	7/8
2-610	5/16	2-620	5/8	2-630	15/16
2-612	3/8	2-622	11/16	2-632	1
2-614	7/16	2-624	3/4		
2-616	1/2	2-626	13/16		



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



3/8" DRIVE UNIVERSAL IMPACT SOCKETS, 6 POINT, SAE

Black Industrial Finish

Product Code	A Size (Inches)	B OAL (Inches)	C Drive End Diameter (Inches)	D Working End Diameter (Inches)	E Broach Depth (Inches)	F Bolt Clearance Depth (Inches)
36212	3/8	2 1/4	1	19/16	9/16	9/16
36214	7/16	2 1/4	1	11/16	9/16	9/16
36216	1/2	2 1/3	1	13/16	9/16	9/16
36218	9/16	2 1/3	1	13/16	9/16	9/16
36220	5/8	2 1/2	1	14/16	9/16	9/16
36222	11/16	2 5/8	1	1	8/16	11/16
36224	3/4	2 5/8	1	1 1/16	9/16	11/16

Fed. Spec: ANSI B107.2

36912 7 Piece 3/8" Drive Universal 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)
36212	3/8	36220	5/8
36214	7/16	36222	11/16
36216	1/2	36224	3/4
36218	9/16		



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove

