



3/8" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, SAE

Black Industrial Finish

Product Code	Size (Inches)	A B C D E F						
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
36108	1/4	1 5/32	3/4	7/16	5/16	21/32	7/32	7/16
36110	5/16	1	3/4	1/2	3/8	17/32	1/4	7/16
36112	3/8	1	3/4	19/32	11/32	17/32	9/32	7/16
36114	7/16	1 3/32	3/4	11/16	3/8	5/8	13/32	7/16
36116	1/2	1 9/32	25/32	25/32	3/8	5/8	7/16	-
36118	9/16	1 1/16	13/16	13/16	9/16	23/32	17/32	-
36120	5/8	1 1/16	15/16	15/16	9/16	23/32	5/8	-
36122	11/16	1 1/16	15/16	15/16	9/16	3/4	21/32	-
36124	3/4	1 1/8	1 1/32	1 1/32	19/32	13/16	23/32	-
36126	13/16	1 9/64	1 1/8	1 1/8	35/64	35/64	3/4	n/a
36128	7/8	1 7/32	1 3/16	1 3/16	5/8	5/8	53/64	n/a
36130	15/16	1 7/32	1 19/64	1 19/64	5/8	5/8	29/32	n/a
36132	1	1 7/32	1 11/32	1 11/32	5/8	5/8	15/16	n/a

Fed. Spec: ANSI B107.2

36902 9 Piece 3/8" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
36108	1/4	36114	7/16	36120	5/8
36110	5/16	36116	1/2	36122	11/16
36112	3/8	36118	9/16	36124	3/4

36903 13 piece 3/8" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
36108	1/4	36114	7/16	36120	5/8
36110	5/16	36116	1/2	36122	11/16
36112	3/8	36118	9/16	36124	3/4
				36126	13/16
				36128	7/8
				36130	15/16
				36132	1



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.



3/8" DRIVE SHALLOW IMPACT SOCKETS, 12 POINT, SAE

Black Industrial Finish

Product Code	Size (Inches)	A B C D E F						
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
35310	5/16	1 1/8	3/4	1/2	3/8	/	1/4	1/2
35312	3/8	1 1/8	3/4	1/2	3/8	/	3/8	1/2
35314	7/16	1 1/8	3/4	5/8	3/8	/	3/8	1/2
35316	1/2	1 1/8	3/4	3/4	3/8	/	3/8	/
35318	9/16	1 1/8	3/4	3/4	3/8	/	1/2	/
35320	5/8	1 1/8	1	15/16	1/2	/	1/2	/
35322	11/16	1 1/8	1	15/16	1/2	/	1/2	/
35324	3/4	1 1/8	1	1	1/2	/	5/8	/
35326	13/16	1 1/8	1 1/8	1	1/2	/	3/4	/
35328	7/8	1 1/8	1 1/8	1 1/8	1/2	/	3/4	/
35330	15/16	1 1/8	1 1/4	1 1/4	1/2	/	3/4	/
35332	1	1 1/8	1 3/8	1 3/8	1/2	/	1	/

36921 12 piece 3/8" Drive Shallow 12 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
35310	5/16	35318	9/16	35326	13/16
35312	3/8	35320	5/8	35328	7/8
35314	7/16	35322	11/16	35330	15/16
35316	1/2	35324	3/4	35332	1



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 or 12 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.