



### 3/8" DRIVE DEEP IMPACT SOCKETS, 6 POINT, METRIC

Black Industrial Finish

Product Code	Size (MM)	A		B		C		D		E		F
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)				
12M-607	7	2 1/8	11/16	7/16	9/32	1 11/16	1/4	1 5/8				
12M-608	8	2 1/8	11/16	1/2	1/4	1 11/16	9/32	1 5/8				
12M-609	9	2 1/8	11/16	9/16	9/32	1 11/16	11/32	1 5/8				
12M-610	10	2 1/8	11/16	5/8	9/32	1 11/16	11/32	1 5/8				
12M-611	11	2 1/8	11/16	21/32	21/64	1 11/16	11/32	1 5/8				
12M-612	12	2 1/8	23/32	23/32	3/8	1 23/32	7/16	-				
12M-613	13	2 1/8	29/32	29/32	7/16	1 3/8	19/32	-				
12M-614	14	2 3/8	13/16	13/16	13/32	1 9/16	1/2	-				
12M-615	15	2 3/8	27/32	27/32	13/32	1 9/16	9/16	-				
12M-616	16	2 3/8	29/32	29/32	13/32	1 9/16	19/32	-				
12M-617	17	2 3/8	31/32	31/32	7/16	1 3/4	5/8	-				
12M-618	18	2 5/8	1	1	7/16	1 3/4	11/16	-				
12M-619	19	2 5/8	1 1/16	1 1/16	9/16	1 3/4	23/32	-				
12M-620	20	2 5/8	1 1/8	1 1/8	15/32	1 3/4	3/4	-				
12M-621	21	2 5/8	1 5/32	1 5/32	1/2	1 3/4	29/32	-				
12M-622	22	2 7/8	1 3/16	1 3/16	1/2	1 31/32	27/32	-				
12M-623	23	2 7/8	1 1/4	1 1/4	17/32	1 31/32	7/8	-				
12M-624	24	2 7/8	1 5/16	1 5/16	19/32	1 31/32	29/32	-				



Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



12M-614 12M-607



MS-12-13H

### MS-12-13H 13 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-612	12	12M-617	17
12M-608	8	12M-613	13	12M-618	18
12M-609	9	12M-614	14	12M-619	19
12M-610	10	12M-615	15		
12M-611	11	12M-616	16		

### MS-12-18H 18 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-613	13	12M-619	19
12M-608	8	12M-614	14	12M-620	20
12M-609	9	12M-615	15	12M-621	21
12M-610	10	12M-616	16	12M-622	22
12M-611	11	12M-617	17	12M-623	23
12M-612	12	12M-618	18	12M-624	24



MS-12-18H

### Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



3/8" DRIVE



### 3/8" HEX DRIVERS

Product Code	Size	Overall Length (Inches)	Product Code Bits	Optional Ret Ring
2MA-612	12 mm	72.7 mm	2MA-612-2	2-1XS
2MA-614	14 mm	72.7 mm	2MA-614-2	2-1XS
2A-616	1/2"	2 7/8"	2A-616-2	2-1XS
2A-618	9/16"	2 7/8"	2A-618-2	2-1XS

### Features

- Designed for use with pneumatic or cordless impact guns
- Optional retaining ring ensures positive attachment to anvil
- Manufactured from special alloy steel and heat treated for optimum strength and durability
- Williams® bits are designed with a precise fit and tight tolerances to prevent slippage and disengagement
- Outperforms one-piece design models - our two-piece design makes replacement economical and convenient
- Bits can be easily replaced by hand - no need to put them in a vice and punch them out with a hammer
- Optional retaining rings available for added protection



2MA-614



2MA-614 with Optional Ret Ring 2-1XS

