



3/8" DRIVE DEEP IMPACT SOCKETS, 6 POINT, METRIC

Black Industrial Finish

Product Code	Size (MM)	A		B		C		D		E		F
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)				
12M-607	7	2 1/8	11/16	7/16	9/32	1 11/16	1/4	1 5/8				
12M-608	8	2 1/8	11/16	1/2	1/4	1 11/16	9/32	1 5/8				
12M-609	9	2 1/8	11/16	9/16	9/32	1 11/16	11/32	1 5/8				
12M-610	10	2 1/8	11/16	5/8	9/32	1 11/16	11/32	1 5/8				
12M-611	11	2 1/8	11/16	21/32	21/64	1 11/16	11/32	1 5/8				
12M-612	12	2 1/8	23/32	23/32	3/8	1 23/32	7/16	-				
12M-613	13	2 1/8	25/32	25/32	7/16	1 3/8	15/32	-				
12M-614	14	2 3/8	13/16	13/16	13/32	1 9/16	1/2	-				
12M-615	15	2 3/8	27/32	27/32	13/32	1 9/16	9/16	-				
12M-616	16	2 3/8	29/32	29/32	13/32	1 9/16	19/32	-				
12M-617	17	2 5/8	31/32	31/32	7/16	1 3/4	5/8	-				
12M-618	18	2 5/8	1	1	7/16	1 3/4	11/16	-				
12M-619	19	2 5/8	1 1/16	1 1/16	9/16	1 3/4	23/32	-				
12M-620	20	2 5/8	1 1/8	1 1/8	15/32	1 3/4	3/4	-				
12M-621	21	2 5/8	1 9/32	1 9/32	1/2	1 3/4	25/32	-				
12M-622	22	2 7/8	1 3/16	1 3/16	1/2	1 31/32	27/32	-				
12M-623	23	2 7/8	1 1/4	1 1/4	17/32	1 31/32	7/8	-				
12M-624	24	2 7/8	1 5/16	1 5/16	19/32	1 31/32	29/32	-				

MS-12-13H 13 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-612	12	12M-617	17
12M-608	8	12M-613	13	12M-618	18
12M-609	9	12M-614	14	12M-619	19
12M-610	10	12M-615	15		
12M-611	11	12M-616	16		

MS-12-18H 18 Piece 3/8" Drive Deep 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
12M-607	7	12M-613	13	12M-619	19
12M-608	8	12M-614	14	12M-620	20
12M-609	9	12M-615	15	12M-621	21
12M-610	10	12M-616	16	12M-622	22
12M-611	11	12M-617	17	12M-623	23
12M-612	12	12M-618	18	12M-624	24

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



MS-12-13H



MS-12-18H

