

CARBIDE, 4 FLUTE LONG LENGTH
SEME72 SERIES

MATERIAL		P											
		NON-ALLOYED STEELS ALLOY STEELS CAST IRON				ALLOY STEELS HEAT RESISTANT STEELS				HARDENED STEELS			
HARDNESS		~ HRc35				HRc35 ~ HRc45				HRc45 ~ HRc55			
STRENGTH		~ 1100N/mm ²				1110 ~ 1500N/mm ²				1500 ~ 2000N/mm ²			
DIA.	LOC	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
1.0	3	19200	180	60	0.002	10940	70	34	0.002	6720	35	21	0.001
1.0	4	19200	180	60	0.002	10940	70	34	0.002	6720	35	21	0.001
1.0	5	19200	180	60	0.002	10940	70	34	0.002	6720	35	21	0.001
1.0	6	17280	145	54	0.002	9850	60	31	0.002	6050	30	19	0.001
1.0	7	17280	145	54	0.002	9850	60	31	0.002	6050	30	19	0.001
1.0	8	17280	130	54	0.002	9850	50	31	0.001	6050	25	19	0.001
1.0	10	17280	130	54	0.002	9850	50	31	0.001	6050	25	19	0.001
1.0	12	15360	100	48	0.002	8760	40	28	0.001	5380	20	17	0.001
1.2	4	16200	205	61	0.003	9230	80	35	0.002	5670	40	21	0.002
1.2	6	16200	205	61	0.003	9230	80	35	0.002	5670	40	21	0.002
1.2	8	14580	165	55	0.003	8310	65	31	0.002	5100	35	19	0.002
1.2	10	14580	145	55	0.002	8310	60	31	0.002	5100	30	19	0.001
1.2	12	14580	145	55	0.002	8310	60	31	0.002	5100	30	19	0.001
1.5	6	13800	215	65	0.004	7870	85	37	0.003	4830	45	23	0.002
1.5	8	12420	195	59	0.004	7080	80	33	0.003	4350	40	20	0.002
1.5	10	12420	175	59	0.004	7080	70	33	0.002	4350	35	20	0.002
1.5	12	12420	155	59	0.003	7080	60	33	0.002	4350	30	20	0.002
1.5	14	12420	155	59	0.003	7080	60	33	0.002	4350	30	20	0.002
1.5	16	11040	120	52	0.003	6290	50	30	0.002	3860	25	18	0.002
2.0	8	10580	240	66	0.006	6050	95	38	0.004	3780	55	24	0.004
2.0	10	10580	240	66	0.006	6050	95	38	0.004	3780	55	24	0.004
2.0	12	9530	195	60	0.005	5440	80	34	0.004	3400	45	21	0.003
2.0	14	9530	195	60	0.005	5440	80	34	0.004	3400	45	21	0.003
2.0	16	9530	175	60	0.005	5440	70	34	0.003	3400	40	21	0.003
2.5	10	8990	260	71	0.007	5170	110	41	0.005	3210	60	25	0.005
2.5	12	8990	260	71	0.007	5170	110	41	0.005	3210	60	25	0.005
2.5	16	8090	210	64	0.006	4650	85	37	0.005	2890	50	23	0.004
2.5	20	8090	185	64	0.006	4650	80	37	0.004	2890	45	23	0.004
2.5	26	7200	145	57	0.005	4130	60	32	0.004	2570	35	20	0.003
3.0	10	7400	275	70	0.009	4280	120	40	0.007	2640	65	25	0.006
3.0	12	7400	275	70	0.009	4280	120	40	0.007	2640	65	25	0.006
3.0	14	7400	275	70	0.009	4280	120	40	0.007	2640	65	25	0.006
3.0	16	6660	250	63	0.009	3860	110	36	0.007	2380	60	22	0.006
3.0	20	6660	225	63	0.008	3860	95	36	0.006	2380	55	22	0.006
3.0	26	6660	200	63	0.008	3860	85	36	0.006	2380	50	22	0.005
3.0	30	6660	200	63	0.008	3860	85	36	0.006	2380	50	22	0.005
4.0	12	6000	335	75	0.014	3410	140	43	0.010	2150	70	27	0.008
4.0	16	6000	335	75	0.014	3410	140	43	0.010	2150	70	27	0.008
4.0	20	6000	335	75	0.014	3410	140	43	0.010	2150	70	27	0.008
4.0	26	5400	270	68	0.013	3070	110	39	0.009	1930	60	24	0.008
4.0	30	5400	270	68	0.013	3070	110	39	0.009	1930	60	24	0.008
5.0	20	5120	430	80	0.021	2900	170	46	0.015	1900	85	30	0.011
5.0	25	5120	430	80	0.021	2900	170	46	0.015	1900	85	30	0.011
5.0	30	4610	350	72	0.019	2610	135	41	0.013	1710	70	27	0.010
5.0	35	4610	350	72	0.019	2610	135	41	0.013	1710	70	27	0.010
5.0	40	4610	310	72	0.017	2610	120	41	0.011	1710	60	27	0.009
6.0	15	4420	515	83	0.029	2520	215	48	0.021	1640	110	31	0.017
6.0	20	4420	515	83	0.029	2520	215	48	0.021	1640	110	31	0.017
6.0	25	4420	515	83	0.029	2520	215	48	0.021	1640	110	31	0.017
6.0	30	4420	440	83	0.025	2520	185	48	0.018	1640	90	31	0.014
6.0	35	3970	395	75	0.025	2270	165	43	0.018	1480	85	28	0.014
6.0	40	3970	350	75	0.022	2270	145	43	0.016	1480	75	28	0.013
6.0	45	3970	350	75	0.022	2270	145	43	0.016	1480	75	28	0.013
8.0	25	3360	550	84	0.041	1900	215	48	0.028	1260	110	32	0.022



DIA. = Diameter
LOC = Length of Cut

RPM = rev./min.
FEED = mm/min.

Vc = m/min.
fz = mm/tooth


CARBIDE, 4 FLUTE LONG LENGTH
SEME72 SERIES

MATERIAL	P												
	NON-ALLOYED STEELS ALLOY STEELS CAST IRON					ALLOY STEELS HEAT RESISTANT STEELS				HARDENED STEELS			
	~ HRc35					HRc35 ~ HRc45				HRc45 ~ HRc55			
	~ 1100N/mm ²					1110 ~ 1500N/mm ²				1500 ~ 2000N/mm ²			
HARDNESS													
STRENGTH													
DIA.	LOC	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
8.0	30	3360	550	84	0.041	1900	215	48	0.028	1260	110	32	0.022
8.0	35	3360	550	84	0.041	1900	215	48	0.028	1260	110	32	0.022
8.0	40	3360	470	84	0.035	1900	185	48	0.024	1260	90	32	0.018
8.0	45	3020	420	76	0.035	1710	165	43	0.024	1130	85	28	0.019
8.0	50	3020	375	76	0.031	1710	145	43	0.021	1130	75	28	0.017
10.0	30	2820	550	89	0.049	1640	215	52	0.033	1010	110	32	0.027
10.0	35	2820	550	89	0.049	1640	215	52	0.033	1010	110	32	0.027
10.0	40	2820	550	89	0.049	1640	215	52	0.033	1010	110	32	0.027
10.0	45	2820	470	89	0.042	1640	185	52	0.028	1010	90	32	0.022
10.0	50	2820	470	89	0.042	1640	185	52	0.028	1010	90	32	0.022
10.0	55	2540	420	80	0.041	1480	165	46	0.028	910	85	29	0.023
10.0	60	2540	375	80	0.037	1480	145	46	0.024	910	75	29	0.021
12.0	35	2300	430	87	0.047	1390	190	52	0.034	840	85	32	0.025
12.0	40	2300	430	87	0.047	1390	190	52	0.034	840	85	32	0.025
12.0	45	2300	365	87	0.040	1390	165	52	0.030	840	70	32	0.021
12.0	50	2300	365	87	0.040	1390	165	52	0.030	840	70	32	0.021
12.0	55	2300	365	87	0.040	1390	165	52	0.030	840	70	32	0.021
12.0	60	2300	325	87	0.035	1390	145	52	0.026	840	65	32	0.019
12.0	65	2070	290	78	0.035	1250	130	47	0.026	760	55	29	0.018
12.0	70	2070	290	78	0.035	1250	130	47	0.026	760	55	29	0.018
14.0	50	2120	345	93	0.041	1230	145	54	0.029	760	65	33	0.021
14.0	60	2120	345	93	0.041	1230	145	54	0.029	760	65	33	0.021
16.0	40	1940	385	98	0.050	1070	150	54	0.035	670	70	34	0.026
16.0	50	1940	385	98	0.050	1070	150	54	0.035	670	70	34	0.026
16.0	60	1940	325	98	0.042	1070	130	54	0.030	670	60	34	0.022
16.0	70	1940	325	98	0.042	1070	130	54	0.030	670	60	34	0.022
16.0	80	1940	290	98	0.037	1070	115	54	0.027	670	55	34	0.021
16.0	90	1750	260	88	0.037	960	100	48	0.026	600	50	30	0.021
16.0	110	1750	260	88	0.037	960	100	48	0.026	600	50	30	0.021
16.0	120	1750	260	88	0.037	960	100	48	0.026	600	50	30	0.021
18.0	50	1680	330	95	0.049	940	130	53	0.035	590	65	33	0.028
18.0	70	1680	280	95	0.042	940	110	53	0.029	590	55	33	0.023
18.0	100	1510	225	85	0.037	850	85	48	0.025	530	45	30	0.021
20.0	50	1420	275	89	0.048	820	110	52	0.034	500	55	31	0.028
20.0	60	1420	275	89	0.048	820	110	52	0.034	500	55	31	0.028
20.0	70	1420	235	89	0.041	820	90	52	0.027	500	45	31	0.023
20.0	80	1420	235	89	0.041	820	90	52	0.027	500	45	31	0.023
20.0	90	1420	205	89	0.036	820	80	52	0.024	500	40	31	0.020
20.0	110	1270	185	80	0.036	730	75	46	0.026	450	35	28	0.019
20.0	120	1270	185	80	0.036	730	75	46	0.026	450	35	28	0.019
22.0	75	1260	205	87	0.041	820	90	57	0.027	500	45	35	0.023
22.0	110	1260	180	87	0.036	820	80	57	0.024	500	40	35	0.020
25.0	70	1100	215	86	0.049	820	110	64	0.034	500	55	39	0.028
25.0	90	1100	185	86	0.042	820	90	64	0.027	500	45	39	0.023
25.0	110	1100	185	86	0.042	820	90	64	0.027	500	45	39	0.023
25.0	120	1100	160	86	0.036	820	80	64	0.024	500	40	39	0.020



 DIA. = Diameter
LOC = Length of Cut

 RPM = rev./min.
FEED = mm/min.

 Vc = m/min.
fz = mm/tooth

CARBIDE, 4 FLUTE LONG LENGTH

- ▶ Due to new coating and new tool geometry, outstanding cutting ability and wear resistance.
- ▶ Excellent performance when cutting prehardened steels, up to HRC55 which are used for molds & dies.
- ▶ Available various length of cut and overall length products.



P.837~838

◇ Call for Availability

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
SEME7201003	1.0	6	3	60
SEME7201004	1.0	6	4	60
SEME7201005	1.0	6	5	60
SEME7201006	1.0	6	6	60
SEME7201007	1.0	6	7	60
SEME7201008	1.0	6	8	60
SEME7201010	1.0	6	10	60
SEME7201012	1.0	6	12	60
SEME7201204	1.2	6	4	60
SEME7201206	1.2	6	6	60
SEME7201208	1.2	6	8	60
SEME7201210	1.2	6	10	60
SEME7201212	1.2	6	12	60
SEME7201506	1.5	6	6	60
SEME7201508	1.5	6	8	60
SEME7201510	1.5	6	10	60
SEME7201512	1.5	6	12	60
SEME7201514	1.5	6	14	60
SEME7201516	1.5	6	16	60
SEME7202008	2.0	6	8	60
SEME7202010	2.0	6	10	60
SEME7202012	2.0	6	12	60
SEME7202014	2.0	6	14	60
SEME7202016	2.0	6	16	60
SEME7202510	2.5	6	10	60
SEME7202512	2.5	6	12	60
SEME7202516	2.5	6	16	60
SEME7202520	2.5	6	20	60

▶ NEXT PAGE


◎ : Excellent ○ : Good

P					H	M	K	N					S	
Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Stainless Steels	Cast Iron	Copper	Graphite	Aluminum	Acrylic	CFRP	Titanium	High Temperature Alloy
~HB225	HB225~325	HRC30~40	HRC40~45	HRC45~55	HRC55~70									
◎	◎	◎	◎	○			○							



CARBIDE, 4 FLUTE LONG LENGTH

- ▶ Due to new coating and new tool geometry, outstanding cutting ability and wear resistance.
- ▶ Excellent performance when cutting prehardened steels, up to HRC55 which are used for molds & dies.
- ▶ Available various length of cut and overall length products.


MG


P.837~838

◇ Call for Availability

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
SEME7202526	2.5	6	26	60
SEME72030163S	3.0	3	16	100
SEME7203010	3.0	6	10	70
SEME7203012	3.0	6	12	70
SEME7203014	3.0	6	14	70
SEME7203016	3.0	6	16	70
SEME7203020	3.0	6	20	70
SEME7203026	3.0	6	26	70
SEME7203030	3.0	6	30	70
SEME72040204S	4.0	4	20	100
SEME7204012	4.0	6	12	70
SEME7204016	4.0	6	16	70
SEME7204020	4.0	6	20	70
SEME7204026	4.0	6	26	70
SEME7204030	4.0	6	30	70
SEME7205020	5.0	6	20	70
SEME7205025	5.0	6	25	70
SEME7205025100	5.0	6	25	100
SEME7205030	5.0	6	30	80
SEME7205035	5.0	6	35	90
SEME7205040	5.0	6	40	100
SEME7206015	6.0	6	15	60
SEME7206015080	6.0	6	15	80
SEME7206020	6.0	6	20	70
SEME7206020090	6.0	6	20	90
SEME7206025	6.0	6	25	75
SEME7206030	6.0	6	30	80
SEME7206030100	6.0	6	30	100


▶ NEXT PAGE

◎ : Excellent ○ : Good

P					H	M	K	N					S	
Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Stainless Steels	Cast Iron	Copper	Graphite	Aluminum	Acrylic	CFRP	Titanium	High Temperature Alloy
~HB225	HB225~325	HRC30~40	HRC40~45	HRC45~55	HRC55~70									
◎	◎	◎	◎	○			○							

CARBIDE, 4 FLUTE LONG LENGTH

- ▶ Due to new coating and new tool geometry, outstanding cutting ability and wear resistance.
- ▶ Excellent performance when cutting prehardened steels, up to HRC55 which are used for molds & dies.
- ▶ Available various length of cut and overall length products.



P.837~838

◇ Call for Availability

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
SEME7206030150	6.0	6	30	150
SEME7206035	6.0	6	35	90
SEME7206040	6.0	6	40	90
SEME7206040120	6.0	6	40	120
SEME7206045	6.0	6	45	150
SEME7208025	8.0	8	25	80
SEME7208030	8.0	8	30	80
SEME7208030100	8.0	8	30	100
SEME7208035	8.0	8	35	90
SEME7208040	8.0	8	40	90
SEME7208040120	8.0	8	40	120
SEME7208040150	8.0	8	40	150
SEME7208045	8.0	8	45	100
SEME7208050	8.0	8	50	100
SEME7208050150	8.0	8	50	150
SEME7210030	10.0	10	30	80
SEME7210030100	10.0	10	30	100
SEME7210035	10.0	10	35	90
SEME7210040	10.0	10	40	90
SEME7210040120	10.0	10	40	120
SEME7210045	10.0	10	45	100
SEME7210050	10.0	10	50	100
SEME7210050150	10.0	10	50	150
SEME7210050200	10.0	10	50	200
SEME7210055	10.0	10	55	150
SEME7210060	10.0	10	60	110
SEME7210060200	10.0	10	60	200
SEME7212035	12.0	12	35	90


▶ NEXT PAGE

◎ : Excellent ○ : Good

P					H	M	K	N					S	
Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Stainless Steels	Cast Iron	Copper	Graphite	Aluminum	Acrylic	CFRP	Titanium	High Temperature Alloy
~HB225	HB225~325	HRc30~40	HRc40~45	HRc45~55	HRc55~70									
◎	◎	◎	◎	○			○							


CARBIDE, 4 FLUTE LONG LENGTH

- ▶ Due to new coating and new tool geometry, outstanding cutting ability and wear resistance.
- ▶ Excellent performance when cutting prehardened steels, up to HRC55 which are used for molds & dies.
- ▶ Available various length of cut and overall length products.



P.837~838

[◇ Call for Availability](#)

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
SEME7212040	12.0	12	40	100
SEME7212040120	12.0	12	40	120
SEME7212045	12.0	12	45	130
SEME7212050	12.0	12	50	100
SEME7212050150	12.0	12	50	150
SEME7212055	12.0	12	55	110
SEME7212060	12.0	12	60	110
SEME7212060150	12.0	12	60	150
SEME7212060200	12.0	12	60	200
SEME7212065	12.0	12	65	150
SEME7212070	12.0	12	70	120
SEME7212070200	12.0	12	70	200
SEME7214050	14.0	16	50	110
SEME7214060	14.0	16	60	150
SEME7216040	16.0	16	40	150
SEME7216050	16.0	16	50	110
SEME7216050150	16.0	16	50	150
SEME7216060	16.0	16	60	120
SEME7216070	16.0	16	70	130
SEME7216070150	16.0	16	70	150
SEME7216070200	16.0	16	70	200
SEME7216080	16.0	16	80	150
SEME7216090	16.0	16	90	150
SEME72160110	16.0	16	110	200
SEME72160120	16.0	16	120	250
SEME7218050	18.0	20	50	120
SEME7218070	18.0	20	70	130
SEME72180100	18.0	20	100	200


▶ NEXT PAGE

◎ : Excellent ○ : Good

P					H	M	K	N					S	
Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Stainless Steels	Cast Iron	Copper	Graphite	Aluminum	Acrylic	CFRP	Titanium	High Temperature Alloy
~HB225	HB225~325	HRC30~40	HRC40~45	HRC45~55	HRC55~70									
◎	◎	◎	◎	○			○							

CARBIDE, 4 FLUTE LONG LENGTH

- ▶ Due to new coating and new tool geometry, outstanding cutting ability and wear resistance.
- ▶ Excellent performance when cutting prehardened steels, up to HRC55 which are used for molds & dies.
- ▶ Available various length of cut and overall length products.



◇ Call for Availability

Unit : mm

EDP No.	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
	D1	D2	L1	L2
SEME7220050	20.0	20	50	110
SEME7220050150	20.0	20	50	150
SEME7220060	20.0	20	60	130
SEME7220070	20.0	20	70	130
SEME7220080	20.0	20	80	150
SEME7220090	20.0	20	90	150
SEME7220090200	20.0	20	90	200
SEME72200110	20.0	20	110	200
SEME72200120	20.0	20	120	250
SEME7222075	22.0	20	75	150
SEME72220110	22.0	20	110	200
SEME7225070	25.0	25	70	150
SEME7225090	25.0	25	90	150
SEME72250110	25.0	25	110	200
SEME72250120	25.0	25	120	250

Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
0~-0.03	h6

© : Excellent ○ : Good

P					H	M	K	N					S	
Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Stainless Steels	Cast Iron	Copper	Graphite	Aluminum	Acrylic	CFRP	Titanium	High Temperature Alloy
~HB225	HB225~325	HRC30~40	HRC40~45	HRC45~55	HRC55~70									
◎	◎	◎	◎	○			○							