

CARBIDE

HSS


**TANK-POWER
END MILLS**
E9921 SERIES

FLAT SHANK

PREMIUM HSS-PM, MULTI FLUTE FINE PITCH ROUGHING EXTENDED NECK CENTER CUTTING

► This TANK-POWER rougher is designed for high production metal removal in a wide range of work piece material. It is suitable for a very broad spectrum of materials having up to high tensile strengths.



◆ U.S.A Stock

Unit : Inch

EDP No.		Mill Diameter	Shank Diameter	Length of Cut	Reach Extended Neck	Overall Length	No. of Flute
UNCOATED	TIAIN COATED						
EP20322	EP20322F	1/2	1/2	1-1/4	3	5	5
EP20402	EP20402F	5/8	5/8	1-5/8	4	6-1/8	5
EP20482	EP20482F	3/4	3/4	1-5/8	4	6-1/4	5
EP20484	EP20484F	3/4	3/4	1-5/8	6	8-1/4	5
EP20642	EP20642F	1	1	2	4	6-1/2	6
EP20643	EP20643F	1	1	2	6	8-1/2	6
EP21161	EP21161F	1-1/4	1 1/4	2	4	6-1/2	6
EP21162	EP21162F	1-1/4	1 1/4	2	6	8-1/2	6

Mill Dia. Tolerance (inch)	
up to 1	0~+.0030
over 1	0~+.0060

◎ : Excellent ○ : Good


Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel
~HRc20	HRc20~30	HRc30~40	HRc40~45	HRc45~55	HRc55~70							
◎	◎	◎				○		◎		◎		

806 • phone:+1-800-765-8665, fax:+1-866-941-8665, Technical Support : 888-868-5988, www.yg1usa.com

CBN
END MILLi-Xmill
END MILLX5070
END MILLS4G MILLS
END MILLSX-SPEED
ROUGHER
END MILLSX-POWER
END MILLSJET-POWER
END MILLSV7 Mill STEEL
END MILLSV7 Mill INOX
END MILLSALU-POWER
END MILLSD-POWER
END MILLSSTANDARD
CARBIDE
END MILLSTANK-POWER
END MILLSSTANDARD
COBALT
& HSS
END MILLSTECHNICAL
DATA


PREMIUM HSS-PM, 3&4 FLUTE 60° HELIX - SIDE CUTTING
E9988 SERIES

MATERIAL	STRUCTURAL STEELS, CARBON STEELS, CAST IRONS		CARBON STEELS, ALLOY STEELS, TOOL STEELS		ALLOY STEELS, TOOL STEELS AUSTENITIC STAINLESS STEELS	
HARDNESS	~HRc20		HRc20 ~ HRc30		HRc30 ~ HRc40	
STRENGTH	500 ~ 800N/mm ²		800 ~ 1000N/mm ²		1000 ~ 1300N/mm ²	
DIAMETER	RPM	FEED	RPM	FEED	RPM	FEED
1/4	3850	7.9	2500	5.3	1900	3.5
5/16	3050	7.9	2100	6.3	1700	3.5
3/8	2700	8.5	1700	6.3	1450	3.8
1/2	1850	9.7	1200	6.3	960	4.1
5/8	1300	11.0	845	8.5	690	5.4
3/4	895	14.6	580	11.9	475	7.9
7/8	720	16.6	475	14.0	380	8.8
1	630	19.0	415	16.0	335	10.0




※ The Feed, in long & extra long types, should be reduced by around 50%.

RPM = rev./min.
FEED = inch/min.

PREMIUM HSS-PM, MULTI FLUTE ROUGHING - SIDE CUTTING
E9990, E9991, E9A86, E9A87, E9921 SERIES

MATERIAL	STRUCTURAL STEELS, CARBON STEELS		STRUCTURAL STEELS, CARBON STEELS, CAST IRONS		CARBON STEELS, ALLOY STEELS, TOOL STEELS		PREHARDENED STEELS, ALLOY STEELS, TOOL STEELS		STAINLESS STEELS	
HARDNESS	~HRc20		HRc20 ~ HRc30		HRc30 ~ HRc35		HRc35 ~ HRc40			
STRENGTH	~800N/mm ²		800 ~ 1000N/mm ²		1000 ~ 1100N/mm ²		1100 ~ 1300N/mm ²			
DIAMETER	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
1/4	2650	7.8	2050	6.3	1450	4.4	1200	3.4	1900	5.6
3/8	1900	13.1	1500	10.1	1050	6.4	885	5.2	1270	8.6
1/2	1450	14.2	1100	11.4	805	7.9	665	6.1	950	9.3
5/8	1150	14.2	905	11.4	630	7.9	525	6.1	760	9.7
3/4	960	14.4	780	11.4	540	7.9	445	6.1	630	9.5
7/8	845	14.5	615	11.4	445	7.8	375	6.1	540	9.3
1	740	14.0	560	10.6	395	7.4	315	6.0	470	9.0



※ The Feed, in long & extra long types, should be reduced by around 50%.

RPM = rev./min.
FEED = inch/min.